

## DLA-12DBC



- ✦ High current data transmission
- ✦ Common mode and differential mode protection
- ✦ Data lines, including those isolated from Earth
- ✦ Compact DIN rail enclosure, high density protection
- ✦ Protection of shield wire
- ✦ Plug-out with line cut-off
- ✦ Location and test categories: D1, C2, C3
- ✦ IEC 61643-21 compliance



	<b>Electrical Characteristics</b>																																								
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Low Capacity Diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RS232, RS485</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>12 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>15 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>&gt; 20 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>&lt; 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance (± 10 %)</td> <td></td> <td>non</td> </tr> <tr> <td>Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)</td> <td>Up</td> <td>35 V</td> </tr> <tr> <td>Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)</td> <td>Up</td> <td>35 V</td> </tr> <tr> <td>Impulse current 2 x 10/350μs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>In</td> <td>5 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>4.7 Ohm</td> </tr> </table>		Network		RS232, RS485	Nominal line voltage	Un	12 V	Max. DC operating voltage	Uc	15 Vdc	Max. frequency	f max.	> 20 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance (± 10 %)		non	Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up	35 V	Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up	35 V	Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA	Nominal discharge current C2 Category	In	5 kA	Line resistance (± 10%)		4.7 Ohm
Network		RS232, RS485																																							
Nominal line voltage	Un	12 V																																							
Max. DC operating voltage	Uc	15 Vdc																																							
Max. frequency	f max.	> 20 MHz																																							
Insertion loss		< 1 dB																																							
Max. load current @25°C	IL	300 mA																																							
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																							
Line inductance (± 10 %)		non																																							
Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up	35 V																																							
Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up	35 V																																							
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA																																							
Nominal discharge current C2 Category	In	5 kA																																							
Line resistance (± 10%)		4.7 Ohm																																							
	<b>Mechanical Characteristics</b>																																								
	<table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+TVS diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminal: cross section 0.5-2.5mm<sup>2</sup></td> </tr> <tr> <td>Format</td> <td></td> <td>Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td>DLAM-12DBC</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> </table>		Technology		GDT+TVS diode	SPD configuration		1-pair+shielded	Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>	Format		Plug-in DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Spare module(s)		DLAM-12DBC	Dimensions		See diagram			
Technology		GDT+TVS diode																																							
SPD configuration		1-pair+shielded																																							
Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>																																							
Format		Plug-in DIN box																																							
Mounting		Symmetrical rail 35 mm (EN 60715)																																							
Housing material		Thermoplastic UL94 V-0																																							
Operating temperature	Tu	-40/+85°C																																							
Protection rating		IP20																																							
Failsafe mode		Short-circuit																																							
Disconnection indicator		Transmission interrupt - default mode 2																																							
Spare module(s)		DLAM-12DBC																																							
Dimensions		See diagram																																							
	<b>Standards</b>																																								
	Standards compliance IEC 61643-21 / EN 61643-21																																								
	<b>Part number</b>																																								
	640221																																								