





CITEL

1-pair DIN rail plug-in Data surge protector

DLA-24DBC



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



G: 3-electrode gas tube
Gb: 2-electrode gas tube
R: Resistor
D: Low Capacity Diode

Electrical Characteristics	
Network	Fipway, WorldFIP, FieldBus-h2
Nominal line voltage	Un 24 V
Max. DC operating voltage	Uc 28 Vdc
Max. frequency	f max. > 20 MHz
Insertion loss	< 1 dB
Max. discharge current max. withstand @ 8/20 µs by pole	I _{max} 20 kA
Line inductance (± 10 %)	non
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	Up 50 V
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	Up 50 V
Max. capacitance	C < 50 pF
Nominal discharge current C2 Category	I _n 5 kA
Max. Load current	I _L 300 mA
Line resistance (± 10 %)	4.7 Ohm
Mechanical Characteristics	
Technology	GDT+TVS diode
SPD configuration	1-pair+shielded
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Protection rating	IP20
Failsafe mode	Short-circuit
Disconnection indicator	Transmission interrupt - default mode 2
Spare module(s)	DLAM-24D3
Dimensions	See diagram
Standards	
Standards compliance	IEC 61643-21 / EN 61643-21
Part number	640321

