


PPV25S-10-600



- ✦ Type 2 surge protector for Photovoltaic
- ✦ PCB mounting
- ✦ I_{max}: 25 kA
- ✦ Remote signaling
- ✦ EN 50539-11 and IEC 61643-31 compliance*



Electrical Characteristics		
SPD type	IEC	2
Max. PV operating voltage	U _{cpv}	600 Vdc
Max. PV operating voltage (star mounting)	U _{cpv}	1200 Vdc
PV Permanent Operating current	I _{cpv}	< 0.1 mA
Nominal discharge current 15 x 8/20 μs impulses	I _n	10 kA
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	25 kA
Current withstand short circuit PV	I _{scpv}	15 000 A
Protection level @ I _n (8/20μs)	U _p	2 kV
Protection level (star mounting) (+/-) / (+/PE or -/PE) @ I _n (8/20μs)	U _p	4 kV
Mechanical Characteristics		
Technology		MOV
Connection to Network		Through soldering pins
Mounting		On Printed Circuit Board
Housing material		Thermoplastic UL94 V-0
Operating temperature	T _u	-40/+85°C
Protection rating		IP20
Disconnection indicator		1 mechanical indicator
Remote signaling of disconnection		Output on changeover contact
Dimensions		See diagram
Weight		0.041 kg
Disconnectors		
Thermal disconnector		Internal
Back-up protection device		Without
Standards		
Standards compliance		IEC 61643-31 / EN 50539-11 *The standard cover devices. PPV/PAC series are components. Compliant when combined is an assembly.
Part number		
8721203		