





# CITEL

## 1-pair Data surge protector unit

### B180-06D3



- ▶ Compact 1-pair surge protection unit
- ▶ 6 V
- ▶ Removable protection circuit
- ▶ Wall mounting and screw connection
- ▶ UL497 A&B



#### Electrical Characteristics

Network		RS422, RS485
Nominal line voltage	Un	6 Vdc
Max. DC operating voltage	Uc	8 Vdc
Max. frequency	f max.	20 MHz
Insertion loss		< 1 dB
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA
Nominal Discharge Current C2 (1.2/50μs / 8/20μs), 10 applications, X-X (Line/Line)	In	5 kA
Protection Level C3 (10/1000μs), 300 applications@10 A, Y-Y (Line/Line)	Up	20 V
Impulse current 2 x 10/350μs Test - D1 Category	limp	2.5 kA
Max. Load current	IL	300 mA
Line resistance		< 4.7 Ohm

#### Mechanical Characteristics

Technology		GDT + R + Diode
SPD configuration		1 pair
Connection to Network		By screw terminal: cross section 0.4-1.5mm <sup>2</sup>
Format		Wall mounting box
Mounting		Wall mounting by screws (not supplied)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit - transmission cut-off - fault mode 2
Spare module(s)		S180-06D3
Dimensions		See diagram

#### Standards

Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B
Certification		UL Listed
Environmental standards		EU RoHS

#### Part number

510102

