



# CITEL

## 'Quarter wave' coaxial protector

### PRC727-4310/MF



- › 'Quarter wave' coaxial protector type 4.3-10
- › Frequency : 690-2700 MHz
- › Low insertion loss
- › I<sub>max</sub> = 40 kA
- › Maintenance free
- › Bi-directional
- › IP65



Electrical Characteristics		
Frequency range	f	690-2700 MHz
Insertion loss		< 0.2 dB
Return loss		> 19 dB
Impedance		50 ohms
VSWR		<1.25:1
Max. load current @25°C	IL	10 A
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I <sub>max</sub>	40 kA
Nominal discharge current <i>C2 Category</i>	I <sub>n</sub>	25 kA
Protection mode(s)		Common mode
Protection level <i>@ I<sub>n</sub> (8/20μs)</i>	Up	< 30 V
Impulse current <i>2 x 10/350μs Test - D1 Category</i>	I <sub>imp</sub>	25 kA
Max Power @f max.		997 W
Max Power @f mini.		1972 W
PIM 3rd order (2x20W)		< -160 dBc
DC Pass		No
Mechanical Characteristics		
Technology		Quarter Wave
Connection to Network		Connector 4.3-10 Male/Female
Mounting		Feedthrough
Housing material		Brass/Surface plating: Cu Zn Sn
Operating temperature	Tu	-40/+85°C
Protection rating		IP65
Failsafe mode		Without
Dimensions		See diagram
Contacts		Bronze/Surface Au-Ag
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497E
RohS compliance		Yes
Part number		
<b>61900</b>		

