




# CITEL

## Compact Type 2 (or 3) DC surge protector - 65 V - Monobloc

### DDCN06S-21YG-65



- DC Power Type 2+3 SPD
- 2-port configuration (series mounting)
- Compact and Cost effective
- In/Imax: 2 kA/6 kA
- Max. load current: 25 A
- Disconnection + AC line cut
- Remote signaling
- EN 61643-11, IEC 61643-11 compliance



V: High-energy varistor  
 GSG: Specific Gas Tube  
 LED: Disconnection indicator  
 Ft: Thermal fuse  
 t°: Thermal disconnection system  
 C: Remote signaling contact

#### Electrical Characteristics

Nominal DC voltage	Un-dc	48 Vdc
Max. DC operating voltage	Uc	65 Vdc
Max. load current @25°C	IL	25 A
Residual Current	Ipe	None
Leakage current to Ground		
Nominal discharge current 15 x 8/20 µs impulses	In	2 kA
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	6 kA
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	4 kV
Connection mode(s)		+/-/PE
Protection level +/- @ In (8/20µs)	Up	0.5 kV
Protection level +/PE (-/PE) @ In (8/20µs)	Up	0.8 kV
Admissible short-circuit current	Isccr	10 000 A

#### Mechanical Characteristics

SPD configuration	Single phase
Connection to Network	By screw terminals: 1.5-10mm <sup>2</sup>
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	Tu -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from DC network
Disconnection indicator	Green LED OFF
Remote signaling of disconnection	output on NC contact
Dimensions	See diagram - 1TE (EN43880)
Weight	0.089 kg

#### Disconnectors

Thermal disconnector	Internal
Back-up protection device	Fuses type gG - 25A

#### Standards

Standards compliance	IEC 61643-11 / prlEC 61643-41
----------------------	-------------------------------

#### Part number

70134052

