



DPVN40CS-21Y-1200



NEW CITEL PV SPD

- ✦ Type 2+3 surge protector for Photovoltaic
- ✦ CTC Technology
- ✦ Discharge currents I_{max}/I_{total} : 40/60 kA (8/20 μ s)
- ✦ Common/Differential mode protection
- ✦ Remote signaling
- ✦ IEC 61643-31, EN 61643-31, EN 50539-11, UL1449 ed.5 compliance
- ✦ Certified EN 61643-31 and IEC 61643-31



V: High-energy varistor
 Ft: Thermal fuse
 C: Remote signal contact
 t*: Thermal disconnection system
 MI: Mechanical disconnection indicator

Electrical Characteristics

SPD type	IEC	2+3
Network		PV 1200 Vdc
Nominal PV voltage	U_{ocstc}	1000 Vdc
Max. PV operating voltage	U_{cpv}	1200 Vdc
Residual Current Leakage current to Ground	I_{pe}	< 0.1 mA
PV Permanent Operating current Current consumption at U_{cpv}	I_{cpv}	< 0.1 mA
Follow current	I_f	None
Nominal discharge current 15 x 8/20 μ s impulses	I_n	20 kA
Max. discharge current max. withstand @ 8/20 μ s by pole	I_{max}	40 kA
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50 μ s - 8/20 μ s	U_{oc}	6 kV
Current withstand short circuit PV	I_{scpv}	15 000 A
Connection mode(s)		+/-/PE
Protection level +/- @ I_n (8/20 μ s)	U_p	4.3 kV
Protection level +/-/PE (-/PE) @ I_n (8/20 μ s)	U_p	4,1 kV
Protection level at 5 kA @ 5 kA (8/20 μ s)	U_p	3,5 kV
Protection level at U_{oc} @ U_{oc} (1.2/50 μ s)	U_p	3,1 kV

Mechanical Characteristics

Technology		MOV
Connection to Network		By screw terminals: 2.5-25mm ² (35mm ²) / by bus
Format		Compact monobloc box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	T_u	-40/+85°C
Protection rating		IP20
Failsafe mode		All pole disconnection from PV network
Disconnection indicator		1 mechanical indicator - Red/Green
Remote signaling of disconnection		Output on changeover contact
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)
Dimensions		See diagram - 2.5TE (EN43880)

Disconnectors

Thermal disconnector		CTC Technology integrated
Back-up protection device		Without

Standards

Standards compliance		IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5
Certification		KEMA

Part number

Part number		65112102
-------------	--	----------