






- SPD Specific Disconnectors (SSD) for short circuit protection of Type 1 AC surge protectors
- Surge current withstand: 12.5 kA @ 10/350µs
- Wide range of short circuit current protected
- Reusable after switch triggered
- Low rated tripping current with time-current characteristics for overcurrent coordination with upstream OCPD and safety disconnect in case of SPD failure



ELEKTRISCHE EIGENSCHAFTEN

Minimum delay tripping current	I_d	3A@<5s
Rated impulse withstand voltage	U_{imp}	6 kV
Minimum instantaneous tripping current	I_i	5A@<0.1s
Nennspannung	U_n	230/400 Vac
Nennableitstoßstrom (8/20) µs / Pol 15 Impulse mit I_n (8/20) µs	I_n	60 kA
Blitzstoßstrom (10/350)µs / Pol max. Blitzableitfähigkeit pro Pol (10/350)µs	I_{imp}	12.5 kA
Vorsicherung integriert		125 A
Ausschaltvermögen		100 000 A
Restspannung	U_p	< 1.9 kV (+SPD)
Bemessungsisolationsspannung	U_i	400 Vac

MECHANISCHE EIGENSCHAFTEN

Bauart		Monoblock-Gehäuse für Hutschienenmontage
Montage auf		35 mm Hutschiene
Temperaturbereich	T_u	-40/+85°C
Schutzart		IP20
Fernmeldesignalisierung (FS)		Potentialfreier Wechsler
Anschlußquerschnitt (FS)		0.75 mm ² max.
Schaltleistung max.		240 V / 2 A (AC) , 24 V / 6 A (DC)
Fernmeldesignalisierung		With attached seperated module
Einbaumaße		Siehe Maßbild

NORMEN

Normkonform nach		GB/T 18802.11 / IEC 61643-11 / NB/T 42150
Zulassungen		CQC

Artikel Nummer

803114