



CITEL

1-pair monobloc Telecom surge protector

DLA-06D3G



- High speed data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	Electrical Characteristics																												
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode SG: Signal ground</p>	<table border="1"> <tr> <td>Network</td> <td>CAN, Profibus DP, RS485</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un 6 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc 8 Vdc</td> </tr> <tr> <td>Cut-off frequency -3dB, 100 ohm system</td> <td>f max. > 80 MHz</td> </tr> <tr> <td>Cut-off frequency -1dB, 100 ohm system</td> <td>f max. > 45 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL 750 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax 20 kA</td> </tr> <tr> <td>Nominal Discharge Current C2 (1.2/50μs / 8/20μs), 10 applications, X-X (Line/Line), X-SG (Line/Signal Ground)</td> <td>In 10 kA</td> </tr> <tr> <td>Nominal Discharge Current C2 (1.2/50μs / 8/20μs), 10 applications, X-C (Line/Earth), SG-C (Signal Ground/Earth)</td> <td>In 10 kA</td> </tr> <tr> <td>Protection Level C3 (10/1000μs), 300 applications@10 A, Y-Y (Line-Line), Y-SG (Line-Signal Ground)</td> <td>Up 30 V</td> </tr> <tr> <td>Protection Level C3 (10/1000μs), 300 applications@10 A, Y-C (Line-Earth), SG-C (Signal Ground-Earth)</td> <td>Up 650 V</td> </tr> <tr> <td>Impulse current D1 (10/350μs), 2 applications, X-C (Line/Earth), X-SG (Line/Signal Ground) and SG-C</td> <td>limp 2.5 kA</td> </tr> <tr> <td>Line/Line Nominal discharge current C2 Category</td> <td>In L/L 10 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td>1.5 Ohm</td> </tr> </table>	Network	CAN, Profibus DP, RS485	Nominal line voltage	Un 6 V	Max. DC operating voltage	Uc 8 Vdc	Cut-off frequency -3dB, 100 ohm system	f max. > 80 MHz	Cut-off frequency -1dB, 100 ohm system	f max. > 45 MHz	Max. load current @25°C	IL 750 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax 20 kA	Nominal Discharge Current C2 (1.2/50μs / 8/20μs), 10 applications, X-X (Line/Line), X-SG (Line/Signal Ground)	In 10 kA	Nominal Discharge Current C2 (1.2/50μs / 8/20μs), 10 applications, X-C (Line/Earth), SG-C (Signal Ground/Earth)	In 10 kA	Protection Level C3 (10/1000μs), 300 applications@10 A, Y-Y (Line-Line), Y-SG (Line-Signal Ground)	Up 30 V	Protection Level C3 (10/1000μs), 300 applications@10 A, Y-C (Line-Earth), SG-C (Signal Ground-Earth)	Up 650 V	Impulse current D1 (10/350μs), 2 applications, X-C (Line/Earth), X-SG (Line/Signal Ground) and SG-C	limp 2.5 kA	Line/Line Nominal discharge current C2 Category	In L/L 10 kA	Line resistance (± 10%)	1.5 Ohm
Network	CAN, Profibus DP, RS485																												
Nominal line voltage	Un 6 V																												
Max. DC operating voltage	Uc 8 Vdc																												
Cut-off frequency -3dB, 100 ohm system	f max. > 80 MHz																												
Cut-off frequency -1dB, 100 ohm system	f max. > 45 MHz																												
Max. load current @25°C	IL 750 mA																												
Max. discharge current max. withstand @ 8/20 μs by pole	Imax 20 kA																												
Nominal Discharge Current C2 (1.2/50μs / 8/20μs), 10 applications, X-X (Line/Line), X-SG (Line/Signal Ground)	In 10 kA																												
Nominal Discharge Current C2 (1.2/50μs / 8/20μs), 10 applications, X-C (Line/Earth), SG-C (Signal Ground/Earth)	In 10 kA																												
Protection Level C3 (10/1000μs), 300 applications@10 A, Y-Y (Line-Line), Y-SG (Line-Signal Ground)	Up 30 V																												
Protection Level C3 (10/1000μs), 300 applications@10 A, Y-C (Line-Earth), SG-C (Signal Ground-Earth)	Up 650 V																												
Impulse current D1 (10/350μs), 2 applications, X-C (Line/Earth), X-SG (Line/Signal Ground) and SG-C	limp 2.5 kA																												
Line/Line Nominal discharge current C2 Category	In L/L 10 kA																												
Line resistance (± 10%)	1.5 Ohm																												
	Mechanical Characteristics <table border="1"> <tr> <td>Technology</td> <td>GDT+TVS diode</td> </tr> <tr> <td>SPD configuration</td> <td>1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td>By spring terminal - max. cross section 2.5mm² / AWG 13 (solid or stranded)</td> </tr> <tr> <td>Format</td> <td>DIN box</td> </tr> <tr> <td>Mounting</td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu -40/+85°C</td> </tr> <tr> <td>Ingress Protection rating</td> <td>IP20 (NEMA 2)</td> </tr> <tr> <td>Failsafe mode</td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Dimensions</td> <td>See diagram</td> </tr> </table>	Technology	GDT+TVS diode	SPD configuration	1-pair+shielded	Connection to Network	By spring terminal - max. cross section 2.5mm ² / AWG 13 (solid or stranded)	Format	DIN box	Mounting	Symmetrical rail 35 mm (EN 60715)	Housing material	Thermoplastic UL94 V-0	Operating temperature	Tu -40/+85°C	Ingress Protection rating	IP20 (NEMA 2)	Failsafe mode	Short-circuit	Disconnection indicator	Transmission interrupt - default mode 2	Dimensions	See diagram						
Technology	GDT+TVS diode																												
SPD configuration	1-pair+shielded																												
Connection to Network	By spring terminal - max. cross section 2.5mm ² / AWG 13 (solid or stranded)																												
Format	DIN box																												
Mounting	Symmetrical rail 35 mm (EN 60715)																												
Housing material	Thermoplastic UL94 V-0																												
Operating temperature	Tu -40/+85°C																												
Ingress Protection rating	IP20 (NEMA 2)																												
Failsafe mode	Short-circuit																												
Disconnection indicator	Transmission interrupt - default mode 2																												
Dimensions	See diagram																												
Standards																													
Standards compliance	IEC 61643-21 / EN 61643-21																												
Part number																													
640191																													

