



CITEL

1-pair monobloc Telecom surge protector

DLA-48D3G



- High speed data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	Electrical Characteristics																																										
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode SG: Signal ground</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>ISDN, 48 V line</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>48 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>53 Vdc</td> </tr> <tr> <td>Cut-off frequency -3dB, 100 ohm system</td> <td>f max.</td> <td>> 80 MHz</td> </tr> <tr> <td>Cut-off frequency -1dB, 100 ohm system</td> <td>f max.</td> <td>> 45 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>750 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 µs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Nominal Discharge Current C2 (1.2/50µs / 8/20µs), 10 applications, X-X (Line/Line), X-SG (Line/Signal Ground)</td> <td>In</td> <td>10 kA</td> </tr> <tr> <td>Nominal Discharge Current C2 (1.2/50µs / 8/20µs), 10 applications, X-C (Line/Earth), SG-C (Signal Ground/Earth)</td> <td>In</td> <td>10 kA</td> </tr> <tr> <td>Protection Level C3 (10/1000µs), 300 applications@10 A, Y-Y (Line-Line), Y-SG (Line-Signal Ground)</td> <td>Up</td> <td>90 V</td> </tr> <tr> <td>Protection Level C3 (10/1000µs), 300 applications@10 A, Y-C (Line-Earth), SG-C (Signal Ground-Earth)</td> <td>Up</td> <td>650 V</td> </tr> <tr> <td>Impulse current D1 (10/350µs), 2 applications, X-C (Line/Earth), X-SG (Line/Signal Ground) and SG-C</td> <td>limp</td> <td>2.5 kA</td> </tr> <tr> <td>Line/Line Nominal discharge current C2 Category</td> <td>In L/L</td> <td>10 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>1.5 Ohm</td> </tr> </table>	Network		ISDN, 48 V line	Nominal line voltage	Un	48 V	Max. DC operating voltage	Uc	53 Vdc	Cut-off frequency -3dB, 100 ohm system	f max.	> 80 MHz	Cut-off frequency -1dB, 100 ohm system	f max.	> 45 MHz	Max. load current @25°C	IL	750 mA	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA	Nominal Discharge Current C2 (1.2/50µs / 8/20µs), 10 applications, X-X (Line/Line), X-SG (Line/Signal Ground)	In	10 kA	Nominal Discharge Current C2 (1.2/50µs / 8/20µs), 10 applications, X-C (Line/Earth), SG-C (Signal Ground/Earth)	In	10 kA	Protection Level C3 (10/1000µs), 300 applications@10 A, Y-Y (Line-Line), Y-SG (Line-Signal Ground)	Up	90 V	Protection Level C3 (10/1000µs), 300 applications@10 A, Y-C (Line-Earth), SG-C (Signal Ground-Earth)	Up	650 V	Impulse current D1 (10/350µs), 2 applications, X-C (Line/Earth), X-SG (Line/Signal Ground) and SG-C	limp	2.5 kA	Line/Line Nominal discharge current C2 Category	In L/L	10 kA	Line resistance (± 10%)		1.5 Ohm
Network		ISDN, 48 V line																																									
Nominal line voltage	Un	48 V																																									
Max. DC operating voltage	Uc	53 Vdc																																									
Cut-off frequency -3dB, 100 ohm system	f max.	> 80 MHz																																									
Cut-off frequency -1dB, 100 ohm system	f max.	> 45 MHz																																									
Max. load current @25°C	IL	750 mA																																									
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA																																									
Nominal Discharge Current C2 (1.2/50µs / 8/20µs), 10 applications, X-X (Line/Line), X-SG (Line/Signal Ground)	In	10 kA																																									
Nominal Discharge Current C2 (1.2/50µs / 8/20µs), 10 applications, X-C (Line/Earth), SG-C (Signal Ground/Earth)	In	10 kA																																									
Protection Level C3 (10/1000µs), 300 applications@10 A, Y-Y (Line-Line), Y-SG (Line-Signal Ground)	Up	90 V																																									
Protection Level C3 (10/1000µs), 300 applications@10 A, Y-C (Line-Earth), SG-C (Signal Ground-Earth)	Up	650 V																																									
Impulse current D1 (10/350µs), 2 applications, X-C (Line/Earth), X-SG (Line/Signal Ground) and SG-C	limp	2.5 kA																																									
Line/Line Nominal discharge current C2 Category	In L/L	10 kA																																									
Line resistance (± 10%)		1.5 Ohm																																									
	<table border="1"> <tr> <td colspan="3">Mechanical Characteristics</td> </tr> <tr> <td>Technology</td> <td></td> <td>GDT+TVS diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By spring terminal - max. cross section 2.5mm² / AWG 13 (solid or stranded)</td> </tr> <tr> <td>Format</td> <td></td> <td>DIN box</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Ingress Protection rating</td> <td></td> <td>IP20 (NEMA 2)</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> </table>	Mechanical Characteristics			Technology		GDT+TVS diode	SPD configuration		1-pair+shielded	Connection to Network		By spring terminal - max. cross section 2.5mm ² / AWG 13 (solid or stranded)	Format		DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Ingress Protection rating		IP20 (NEMA 2)	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Dimensions		See diagram						
Mechanical Characteristics																																											
Technology		GDT+TVS diode																																									
SPD configuration		1-pair+shielded																																									
Connection to Network		By spring terminal - max. cross section 2.5mm ² / AWG 13 (solid or stranded)																																									
Format		DIN box																																									
Mounting		Symmetrical rail 35 mm (EN 60715)																																									
Housing material		Thermoplastic UL94 V-0																																									
Operating temperature	Tu	-40/+85°C																																									
Ingress Protection rating		IP20 (NEMA 2)																																									
Failsafe mode		Short-circuit																																									
Disconnection indicator		Transmission interrupt - default mode 2																																									
Dimensions		See diagram																																									
Standards																																											
Standards compliance		IEC 61643-21 / EN 61643-21																																									
Part number																																											
640194																																											

