



ULiQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

Citel America Inc

10108 USA Today Way, Miramar FL 33025

Cat No(s): DS215S-230/G

| <u>SPD</u> <u>Type</u> | <u>Volts</u> <u>(V)</u> | <u>AC/DC</u> <u>DC PV</u> | <u>Phase</u> | <u>Amps</u> <u>(A)</u> | <u>Ambient</u> <u>Min(°C)</u> | <u>Ambient</u> <u>Max(°C)</u> | <u>Mode</u> | <u>VPR</u> <u>(Vpk)</u> | <u>MLV</u> <u>(Vpk)</u> | <u>MCOV</u> <u>(V)</u> | <u>Vn</u> <u>(Vdc)</u> | <u>In</u> <u>(kA)</u> | <u>SCCR</u> <u>(kA)</u> | <u>Notes</u> |
|---------------------------|----------------------------|------------------------------|--------------|---------------------------|----------------------------------|----------------------------------|-------------|----------------------------|----------------------------|---------------------------|---------------------------|--------------------------|----------------------------|--------------|
| 4CA (5) | 400/230 | AC | 3Y | n/a | -35 | 60 | L-N | - | 800 | 255 | n/a | 5 | n/a | 1 |
| | | | | | | | L-G | - | 1370 | 255 | n/a | | | |
| | | | | | | | N-G | - | 1270 | 255 | n/a | | | |

Evaluated to: UL 1449 4th Ed. Rev: 2016-03-17 and CSA Electrical Certification Notice 516/CSA C22.2 No. 8 13

- - L-L modes may also be labeled as L-N modes

Note 1 - Suitable for Factory wiring only.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report

Date: 2012-05-12

Last 2016-03-29

Revised:

© 2018 UL LLC

