



# UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

## Citel America Inc

10108 USA Today Way, Miramar FL 33025

**Cat No(s): DAC50S-40-440**

<u>SPD</u> <u>Type</u>	<u>Volts</u> <u>(V)</u>	<u>AC/DC</u> <u>DC PV</u>	<u>Phase</u>	<u>Amps</u> <u>(A)</u>	<u>Ambient</u> <u>Min(°C)</u>	<u>Ambient</u> <u>Max(°C)</u>	<u>Mode</u>	<u>VPR</u> <u>(Vpk)</u>	<u>MLV</u> <u>(Vpk)</u>	<u>MCOV</u> <u>(V)</u>	<u>Vn</u> <u>(Vdc)</u>	<u>In</u> <u>(kA)</u>	<u>SCCR</u> <u>(kA)</u>	<u>Notes</u>
4CA	400/230	AC	3Y	n/a	-40	85	L-L	-	4140	880	n/a	20	n/a	1
							L-N	-	4140	880	n/a			
							L-G	-	2750	440	n/a			
							N-G	-	2750	440	n/a			

Evaluated to: UL 1449 4th Ed. Rev: 2018-08-01

Note 1 - Suitable for Factory wiring only.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2020-12-02

Last Revised: 2020-12-15

© 2021 UL LLC

