



UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

Citel America Inc

10108 USA Today Way, Miramar FL 33025

Cat No(s): DAC50S-40-275

<u>SPD</u> Type	<u>Volts</u> (V)	<u>AC/DC</u> DC PV	<u>Phase</u>	<u>Amps</u> (A)	<u>Ambient</u> Min(°C)	<u>Ambient</u> Max(°C)	<u>Mode</u>	<u>VPR</u> (Vpk)	<u>MLV</u> (Vpk)	<u>MCOV</u> (V)	<u>Vn</u> (Vdc)	<u>In</u> (kA)	<u>SCCR</u> (kA)	<u>Notes</u>
4CA	400/230	AC	3Y	n/a	-40	85	L-L	-	3080	550	n/a	20	n/a	1
							L-N	-	3080	550	n/a			
							L-G	-	2260	275	n/a			
							N-G	-	2260	275	n/a			

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08

Note 1 - Suitable for Factory wiring only.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2020-12-02

Last Revised: 2021-09-30

© 2022 UL LLC

