






DAC40CS-11

# DAC40CS SERIES

- Compact single phase Type 2 surge protector
- Common/Differential mode
- Remote signaling contact
- EN 61643-11, IEC 61643-11 certified
- UL1449 ed.5 compliance



DAC40CS-xx-xxx



V : High energy varistor  
Ft : Thermal fuse  
C : Contact for remote signal  
t° : Thermal disconnection system  
GSG: Specific gas tube  
MI : Disconnection indicator

## Characteristics

CITEL Model		DAC40CS-20-440	DAC40CS-11-275	DAC40CS-11-150
Description		Compact 1-phase Type 2 surge protector - Pluggable		
Network		230 V single-phase		
Protection mode		L/PE and N/PE	L/N and N/PE	L/N and N/PE
AC system		IT	TT-TN	TT-TN
Max. AC operating voltage	Uc	440 Vac	275 Vac	150 Vac
Temporary Over Voltage (TOV)	UT	580 Vac	335 Vac	180 Vac
Characteristic - 5 sec.		withstand	withstand	withstand
Temporary Over Voltage (TOV)	UT	770 Vac	440 Vac	230 Vac
Characteristic - 120mn		disconnection	disconnection	disconnection
Temporary Over Voltage N/PE (TOV HT)	UT	-	1200 V/300A/200 ms withstand	1200 V/300A/200 ms withstand
Residual current - Leakage current at Uc	Ipe	< 1 mA	None	None
Follow current	If	None	None	None
Nominal discharge current 15 x 8/20 μs impulses	In	20 kA	20 kA	20 kA
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	40 kA	40 kA	40 kA
Total discharge current - @8/20μs	Itotal	80 kA	40 kA	40 kA
Protection level @In (8/20μs)	Up L/N	-	1.25 kV	0.9 kV
	Up N/PE	1.8 kV	1.5 kV	1.5 kV
	Up L/PE	1.8 kV	-	-
Admissible short-circuit current	Iscrr	10 000 A	10 000 A	10 000 A
<b>Associated disconnectors</b>				
Thermal disconnector		internal		
Fuses		50 A min. - 125 A max. - Type gG		
Existing upstream ground fault breaker (if any)		Type "S" or delayed		
<b>Mechanical characteristics</b>				
Dimensions		see diagram, 1TE (DIN43880)		
Connection to Network		by screw terminals: L/n = 1.5-10mm <sup>2</sup> (16 mm <sup>2</sup> ) / PE = 2.5-25mm <sup>2</sup> (35 mm <sup>2</sup> rigid)		
Failsafe mode		Disconnection from network		
Disconnection indicator		1 mechanical indicator Green/Red		
Max. voltage/current for remote signaling		250 V/0.5 A (AC) / 30 V/3 A (DC)		
Wiring for remote signaling		Max. 1.5 mm <sup>2</sup>		
Mounting		Symmetrical rail 35 mm (EN60715)		
Operating temperature		-40/+85°C		
Protection rating		IP20		
Housing material		Thermoplastic UL94 V-0		
Spare unit		MDAC40C-20-440	MDAC40C-11-275	MDAC40C-11-150
<b>Standards</b>				
Certification		KEMA		
Compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5		
<b>Part number</b>				
		821510421	821520221	821520121