

*Type 2 AC surge protector - 3-phase+N*

# DAC50VG-40-275




- Type 2 + 3 AC surge protector
- VG Technology
- In: 20 kA
- No leakage current
- Pluggable module for each phase
- Remote signaling (option)
- Optimized to TOV
- EN 61643-11, IEC 61643-11 certified
- UL1449 ed.5 compliance




**V: High-energy varistor**
**Ft: Thermal fuse**
**t°: Thermal disconnection system**
**MI: Disconnection indicator**

| **Electrical Characteristics** | | |
|---|---|---|
| SPD type | IEC | 2+3 |
| Network | | 230/400V |
| AC system | | TNS |
| Max. AC operating voltage | Uc | 275 Vac |
| Temporary Over Voltage (TOV) Characteristics - 5 sec.<br>*Without disconnection* | UT | 335 Vac withstand |
| Temporary Over Voltage (TOV) Characteristics - 120 mn<br>*Without disconnection or with safety disconnection* | UT | 440 Vac withstand |
| Residual Current<br>*Leakage current to Ground* | Ipe | None |
| Follow current | If | None |
| Nominal discharge current<br>*15 x 8/20 µs impulses* | In | 20 kA |
| Max. discharge current<br>*max. withstand @ 8/20 µs by pole* | Imax | 50 kA |
| Total Maximum discharge current<br>*max. total withstand @ 8/20 µs* | Imax Total | 200 kA |
| Withstand on Combination waveform IEC 61643-11<br>*Class III test: 1.2/50µs - 8/20µs* | Uoc | 6 kV |
| Connection mode(s) | | L/PE and N/PE |
| Protection level N/PE<br>*@ In (8/20µs)* | Up N/PE | 1.5 kV |
| Protection level L/PE<br>*@ In (8/20µs)* | Up L/PE | 1.5 kV |
| Protection level N/PE at 5 kA<br>*@ 5 kA (8/20µs)* | Up-5kA | 0.7 kV |
| Residual voltage L/PE at 5 kA<br>*@ 5 kA (8/20µs)* | Up-5kA | 0.7 kV |
| Admissible short-circuit current | Isccr | 50 000 A |
| **Mechanical Characteristics** | | |
| Technology | | VG Technology (MOV+GSG) |
| SPD configuration | | 3-phase+Neutral |
| Connection to Network | | By screw terminals: 2.5-25mm² (35mm² rigid) |
| Format | | Plug-in modular box |
| Mounting | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection from AC network |
| Disconnection indicator | | 1 mechanical indicator by pole - Red/Green |
| Spare module(s) | | MDAC50VG-275 |
| Remote signaling of disconnection | | option DAC50VGS-40-275 : output on changeover contact |
| Dimensions | | See diagram - 4TE (EN43880) |
| **Disconnectors** | | |
| Thermal disconnector | | Internal |
| Installation ground fault breaker | | Type 'S' or delayed |
| Back-up protection device | | 50 A min. - 160 A max. - Fuses Type gG |
| **Standards** | | |
| Standards compliance | | IEC 61643-11 / EN 61643-11 / UL1449 ed.5 |
| Certification | | KEMA |
| **Part number** | | |
| **821130214** | | |