

Type 2 AC surge protector - 1-pole - pluggable


DS41-1000/WD



- Type 2 AC surge protector
- In : 15 kA
- Imax : 30 kA
- Pluggable module for each phase
- Remote signaling option
- NF EN 61643-11, IEC 61643-11 compliance

CE





V: High-energy varistor
Ft: Thermal fuse
t°: Thermal disconnection system
MI: Disconnection indicator

Electrical Characteristics		
SPD type	IEC	2
Network		1000 Vac
Nominal line voltage	Un	1000 Vac
Max. AC operating voltage	Uc	1100 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. *Without disconnection*	UT	1450 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn *Without disconnection or with safety disconnection*	UT	1900 Vac disconnection
Residual Current *Leakage current to Ground*	Ipe	< 0.5 mA
Follow current	If	None
Nominal discharge current *15 x 8/20 µs impulses*	In	15 kA
Max. discharge current *max. withstand @ 8/20 µs by pole*	Imax	30 kA
Connection mode(s)		L/PE
Protection mode(s)		Common mode
Protection level *@ In (8/20µs)*	Up	5.1 kV
Admissible short-circuit current	Isccr	25 000 A
Mechanical Characteristics		
Technology		MOV
SPD configuration		Single phase
Connection to Network		By screw terminals: 2.5-25mm² / by bus
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Housing material		Thermoplastic UL94 V-0
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection from AC network
Disconnection indicator		1 mechanical indicator
Spare module(s)		DSM40-1000/WD
Remote signaling of disconnection		option DS41S-1000/WD : output on changeover contact
Dimensions		See diagram
Disconnectors		
Thermal disconnector		Internal
Installation ground fault breaker		Type 'S' or delayed
Back-up protection device		Fuses type gG - 50 A
Standards		
Standards compliance		IEC 61643-11 / EN 61643-11
Certification		
Part number		
4629012125		