

*Type 1+2+3 AC surge protector - Single Phase - With Surge Counter integrated*

# DACN1-25CVGS-11-385/SC




- Type 1 + 2+3 AC surge protector
- VG Technology
- Iimp: 25 kA on 10/350µs impulse
- In: 25 kA
- Optimized to TOV
- No leakage current
- Monobloc
- Remote signaling
- EN 61643-11, IEC 61643-11 Certified




**V: High-energy varistor**
**GSG: Specific gas tube**
**Ft: Thermal fuse**
**C: Remote signaling contact**
**t°: Thermal disconnection system**
**MI: Disconnection indicator**

| Electrical Characteristics | | |
|---|---|---|
| SPD type | IEC | 1+2+3 |
| Network | | 230/400V |
| AC system | | TT-TN |
| Max. AC operating voltage | Uc | 385 Vac |
| Temporary Over Voltage (TOV) Characteristics - 5 sec.<br>*Without disconnection* | UT | 500 Vac withstand |
| Temporary Over Voltage (TOV) Characteristics - 120 mn<br>*Without disconnection or with safety disconnection* | UT | 650 Vac disconnection |
| Temporary Over Voltage N/PE (TOV HT)<br>*Without disconnection or with safety disconnection* | UT | 1200 V/300A/200 ms withstand |
| Residual Current<br>*Leakage current to Ground* | Ipe | None |
| Follow current | If | None |
| Nominal discharge current<br>*15 x 8/20 µs impulses* | In | 25 kA |
| Max. discharge current<br>*max. withstand @ 8/20 µs by pole* | Imax | 100 kA |
| Impulse current by pole<br>*max. withstand 10/350µs by pole* | Iimp | 25 kA |
| Total lightning current<br>*max. total withstand @ 10/350µs* | Itotal | 50 kA |
| Withstand on Combination waveform IEC 61643-11<br>*Class III test: 1.2/50µs - 8/20µs* | Uoc | 6 kV |
| Protection level L/N<br>*@ In (8/20µs)* | Up L/N | 1.5 kV |
| Protection level N/PE<br>*@ In (8/20µs)* | Up N/PE | 1.5 kV |
| Minimum current sensibility | Itc | 100 A |
| Admissible short-circuit current | Isccr | 50 000 A |
| **Mechanical Characteristics** | | |
| Technology | | VG Technology (MOV+GSG) |
| SPD configuration | | Single phase |
| Connection to Network | | By screw terminals: 2.5-25mm² (35mm² rigid) |
| Format | | Monobloc modular box |
| Mounting | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection from AC network |
| Disconnection indicator | | 1 mechanical indicator - Red/Green |
| Remote signaling of disconnection | | Output on changeover contact |
| Wiring for remote signaling | | 1.5 mm² max. |
| Max. Voltage/Current for remote signaling | | 250 V / 0.5 A (AC) / 30 V / 3 A (DC) |
| **Disconnectors** | | |
| Thermal disconnector | | Internal |
| Installation ground fault breaker | | Type 'S' or delayed |
| Back-up protection device | | 315 A max. - Fuses Type gG / or SFD1-25S |
| **Standards** | | |
| Standards compliance | | EN 61643-11 / IEC 61643-11 |
| Certification | | KEMA |
| **Part number** | | |
| **64193** | | |