
AK1.K5x10.K5x10.15CS-31-275



- Universal small housing for individual cable entry with consideration of practical cross-sections
- Internal terminal design allows spur or V-wiring (series)
- Suitable for TNS-TT mains types
- Integrated DAC15CS-31-275
- Compact type 3 SPD
- Discharge capacity per pole: In= 5kA (8/20µs); Imax= 15kA (8/20µs)
- Pluggable protection modules
- Remote signalling as standard



Electrical Characteristics		
SPD type	IEC	3
Nominal line voltage	Un	230/400 Vac
Max. AC operating voltage	Uc	275 Vac
Max. load current *if series connection*	IL	bis 57 A (Verlegeart beachten)
Surge protection device		DAC15CS-31-275** (internally pre-wired)
Nominal frequency	fn	50 Hz
Mechanical Characteristics		
Housing material		Thermoplastic UL94 V-0
Protection rating		IP65
Dimensions		See diagram - 3 TE (EN43880)
Entrance		Screw terminals max. 10mm² (re or rm)
Outgoing		Screw terminals max. 10mm² (re or rm)
Earth connection terminal		Screw terminal max. 10mm² (re or rm)
Ambient temperature		-25°C bis +40°C / 24h up to max. 35°C
Cable gland		Double diaphragm connector Cable glands M16 / M20 / M25
Humidity		Relative humidity (25°C) 5% to 95% / Max. relative air humidity (40°C) 50%.
Shock resistance		IK 08
Standards		
Standards compliance		IEC 61643-11
Part number		
159145		