

*Type 2 AC surge protector + RFI filtering*

# DS41HFS-230




- Type 2 AC surge protector
- RFI filtering integrated
- In : 20 kA
- Imax : 40 kA
- Pluggable module
- Remote signaling option
- EN 61643-11, IEC 61643-11, UL1449 ed.5 compliance




**V: MOV**
**Ft: Thermal fuse**
**C: Remote signaling contact**
**t°: Thermal disconnection system**
**RFI : RFI filtering**

| Electrical Characteristics | | |
|---|---|---|
| SPD type | IEC | 2 |
| Network | | 230/400V |
| Nominal line voltage | Un | 230 Vac |
| Max. AC operating voltage | Uc | 255 Vac |
| Temporary Over Voltage (TOV) Characteristics - 5 sec.<br>*Without disconnection* | UT | 335 Vac withstand |
| Temporary Over Voltage (TOV) Characteristics - 120 mn<br>*Without disconnection or with safety disconnection* | UT | 440 Vac disconnection |
| Follow current | If | None |
| Nominal discharge current<br>*15 x 8/20 µs impulses* | In | 20 kA |
| Max. discharge current<br>*max. withstand @ 8/20 µs by pole* | Imax | 40 kA |
| RFI Filtering | | 0.1 - 30 MHz |
| Connection mode(s) | | L/N or N/PE |
| Protection mode(s) | | Common Mode or Differential Mode |
| Protection level<br>*@ In (8/20µs)* | Up | 1.25 kV |
| Residual voltage at 5 kA<br>*@ 5 kA (8/20µs)* | Up-5kA | 1 kV |
| Max. capacitance | C | 0,22 µF |
| Admissible short-circuit current | Isccr | 25 000 A |
| **Mechanical Characteristics** | | |
| Technology | | MOV+Filter |
| SPD configuration | | Single phase |
| Connection to Network | | By screw terminals: 2.5-25mm² |
| Format | | Plug-in modular box |
| Mounting | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection from AC network |
| Disconnection indicator | | 1 mechanical indicator |
| Spare module(s) | | DSM40HF-230 |
| Remote signaling of disconnection | | Output on changeover contact |
| Dimensions | | See diagram |
| **Disconnectors** | | |
| Thermal disconnector | | Internal |
| Installation ground fault breaker | | Type 'S' or delayed |
| Back-up protection device | | Fuses type gG - 50 A |
| **Standards** | | |
| Standards compliance | | IEC 61643-11 / EN 61643-11 / UL1449 ed.5 |
| Certification | | CSA |
| **Part number** | | |
| **461590** | | |

# DS41HFS-230