

# *2-pair DIN rail plug-in Data surge protector*

## DLA2-24D3





- Din rail plug-in surge protector
- 2-pair
- Un: 24 V
- Shield wire protection
- Without line cut-off
- IEC 61643-21 compliance
- UL497B




**G: 3-electrode gas tube**
**Gb: 2-electrode gas tube**
**R: Resistor**
**D: Clamping diode**



| **Electrical Characteristics** | | |
|---|---|---|
| Network | | 4-20mA, Liaison 24V |
| Nominal line voltage | Un | 24 V |
| Max. DC operating voltage | Uc | 28 Vdc |
| Cut-off frequency<br>*-3dB, 100 ohm system* | f max. | > 115 MHz |
| Cut-off frequency<br>*-1dB, 100 ohm system* | f max. | > 50 MHz |
| Max. load current @25°C | IL | 300 mA |
| Max. discharge current<br>*max. withstand @ 8/20 µs by pole* | Imax | 20 kA |
| Nominal discharge current<br>*C2 Category* | In | 5 kA |
| Protection Level<br>*C3 (10/1000µs), 300 applications@10 A, Y-Y (Line/Line)* | Up | 40 V |
| Protection Level<br>*C3 (10/1000µs), 300 applications@10 A, Y-C (Line/Earth)* | Up | 650 V |
| Impulse current<br>*D1 (10/350µs), 2 applications, X-C (Line/Earth)* | Iimp | 5 kA |
| Line resistance (± 10%) | | 4.7 Ohm |
| **Mechanical Characteristics** | | |
| Technology | | GDT+TVS diode |
| SPD configuration | | 2-pairs+shielded |
| Connection to Network | | By screw terminal: cross section 0.5-2.5mm² |
| Format | | Plug-in DIN box |
| Mounting | | Symmetrical rail 35 mm (EN 60715) |
| Housing material | | Thermoplastic UL94 V-0 |
| Operating and storage temperature | | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Short-circuit |
| Disconnection indicator | | Transmission interrupt - default mode 2 |
| Spare module(s) | | DLA2M-24D3 |
| Dimensions | | See diagram |
| **Standards** | | |
| Standards compliance | | IEC 61643-21 / EN 61643-21 / UL497B |
| Certification | | UL Listed |
| Environmental standards | | EU RoHS |
| **Part number** | | |
| **640311** | | |