



G: Gas tube
 D: Clamping diode network
 V: Varistor
 LED: Status indicator
 L: Inductor

Electrical Characteristics

| | | |
|---|---------|--------------------------|
| SPD type | | 2+3 |
| Network | | 24 Vac/Vdc |
| Nominal line voltage | Un | 24 Vac/Vdc |
| Max. DC operating voltage | Uc | 30 Vac/Vdc |
| Insertion loss | | < 0.1 dB |
| Max. load current @25°C | IL | 5 A |
| Nominal discharge current 15 x 8/20 μs impulses | In | 5 kA |
| Max. discharge current max. withstand @ 8/20 μs by pole | Imax | 10 kA |
| Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs | Uoc | 10 kV / 5 kA |
| Protection mode(s) | | Common/Differential mode |
| Protection level @ In (8/20μs) | Up | 0.22 kV |
| Protection level Following the test category C3 (IEC61643-21) - Line/Line | Up | 20 V |
| Protection level L/N @ In (8/20μs) | Up L/N | 0.22 kV |
| Protection level L/PE @ In (8/20μs) | Up L/PE | 0.22 kV |
| Nominal discharge current C2 Category | In | 2.5 kA |

ELEC

| | | |
|---------|--|--------------|
| Network | | Signal video |
|---------|--|--------------|

ELEC

| | | |
|---------------------------|----|-------|
| Max. DC operating voltage | Uc | 6 Vdc |
|---------------------------|----|-------|

ELEC

| | | |
|----------------|--------|---------|
| Max. frequency | f max. | 100 Mhz |
|----------------|--------|---------|

ELEC

| | | |
|----------------|--|-------|
| Insertion loss | | < 1dB |
|----------------|--|-------|

ELEC

| | | |
|------------------------|----|--------|
| Max. load current@25°C | IL | 300 mA |
|------------------------|----|--------|

ELEC

| | | |
|---|----|------|
| Nominal discharge current 15 x 8/20 μs impulses | In | 5 kA |
|---|----|------|

ELEC

| | | |
|---|------|-------|
| Max. discharge current max. withstand @ 8/20 μs by pole | Imax | 10 kA |
|---|------|-------|

ELEC

| | | |
|--------------------------------|----|------|
| Protection level @ In (8/20μs) | Up | 20 V |
|--------------------------------|----|------|

ELEC

| | | |
|---------|--|---------------------|
| Network | | 1 pair signal 0-5 V |
|---------|--|---------------------|

ELEC

| | | |
|---------------------------|----|-------|
| Max. DC operating voltage | Uc | 8 Vdc |
|---------------------------|----|-------|

ELEC

| | | |
|----------------|--------|--------|
| Max. frequency | f max. | 16 MHz |
|----------------|--------|--------|

ELEC

| | | |
|----------------|--|-------|
| Insertion loss | | < 1dB |
|----------------|--|-------|

ELEC

| | | |
|------------------------|----|--------|
| Max. load current@25°C | IL | 300 mA |
|------------------------|----|--------|

ELEC

| | | |
|---|------|------|
| Max. discharge current max. withstand @ 8/20 μs by pole | Imax | 5 kA |
|---|------|------|

ELEC

| | | |
|--------------------------------|----|------|
| Protection level @ In (8/20μs) | Up | 20 V |
|--------------------------------|----|------|

ELEC

| | | |
|---------------------------------------|----|--------|
| Nominal discharge current C2 Category | In | 2.5 kA |
|---------------------------------------|----|--------|

Mechanical Characteristics

| | | |
|------------|--|---------|
| Technology | | MOV+GDT |
|------------|--|---------|

| | | |
|-----------------------|--|---------------------------------|
| Connection to Network | | By screw terminals: 2.5mm² max. |
|-----------------------|--|---------------------------------|

MSP-VM24

| | | |
|-----------------------------|----|--|
| Format | | DIN rail or flange |
| Mounting | | DIN rail or plate (flange) |
| Housing material | | Anodized aluminum |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | | IP20 |
| Failsafe mode | | Disconnection and Power cut off |
| Disconnection indicator | | Green LED OFF and line cut off |
| Voltage/operating indicator | | Green led(s) on |
| Dimensions | | See diagram |
| Weight | | 0.184 kg |
| Disconnectors | | |
| Thermal disconnecter | | Internal |
| Standards | | |
| Standards compliance | | IEC 61643-11 / EN 61643-11 / UL1449 ed.5 |
| Part number | | |
| 420402 | | |