



# Coaxial surge protector DC-3.5 GHz

# CITEL

## P8AX50-N/FF



- RF coaxial surge protector
- 3.5 GHz
- Connectors: N
- Low insertion loss
- Removable GDT
- DC-pass
- Bi-directional protection



	<b>Electrical Characteristics</b>	
	Max. DC operating voltage	Uc 400 Vdc
	Impedance	50 ohms
Residual Current <i>Leakage current to Ground</i>	Ipe	None
Max. discharge current <i>max. withstand @ 8/20 µs by pole</i>	Imax	20 kA
Protection level <i>@ 1kV/µs (C3)</i>	Up	< 1200 V
Impulse current <i>2 x 10/350µs Test - D1 Category</i>	Iimp	1 kA
Nominal discharge current <i>C2 Category</i>	In	5 kA
Max Power		780 W
Typical let through energy <i>(50 ohms) input 4kV 1.2/50µs - 2kA 8/20µs</i>		1100 µJ
DC Pass		Yes
Insulation resistance	IR	≥10 GOhms
<b>Mechanical Characteristics</b>		
Technology		Gas discharge tube
Connection to Network		Connector N Female/Female
Mounting		Feedthrough
Housing material		Brass/Surface plating: Cu Zn Sn
Operating temperature	Tu	-40/+85°C
Protection rating		IP65
Failsafe mode		Short-circuit
Disconnection indicator		Transmission interrupt
Spare module(s)		BBHF-500V
Dimensions		See diagram
Contacts		Bronze/Surface Au-Ag
<b>Standards</b>		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497E
<b>Part number</b>		
60017		

