





- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



G: 3-electrode gas tube
 Gb: 2-electrode gas tube
 R: Resistor
 D: Clamping diode

Electrical Characteristics

Network	RTC, ADSL2, VDSL2
Nominal line voltage	Un 150 V
Max. DC operating voltage	Uc 170 Vdc
Max. frequency	f max. 100 Mhz
Insertion loss	< 1 dB
Max. load current @25°C	IL 2.4 A
Max. discharge current max. withstand @ 8/20 µs by pole	I _{max} 20 kA
Line inductance	No
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up < 750 V
Max. capacitance	C < 5 pF
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp} 5 kA
Nominal discharge current C2 Category	I _n 5 kA
Line resistance	0 Ohm

Mechanical Characteristics

Technology	GDT+Clamping diode
SPD configuration	1-pair+shielded
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²
Format	Plug-in DIN box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating and storage temperature	-40/+85°C
Protection rating	IP20
Failsafe mode	Short-circuit
Disconnection indicator	Transmission interrupt - default mode 2
Spare module(s)	DLMAM-170G
Dimensions	See diagram
Standards	
Standards compliance	IEC 61643-21 / EN 61643-21
Part number	640165

