



CITEL

Ultra Compact Type 3 hard wired surge protector

MSB6-400



- Compact type 3 surge protector
- Wall mounting and hard wired connection
- Status indicators
- IP20
- EN 61643-11, IEC 61643-11 and UL1449 ed.5 compliance



	Electrical Characteristics																																																	
<p>V: Varistor GSG: Specific gas tube Ft: Thermal fuse Buzzer: Audible disconnection indicator t*: Thermal system disconnection</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>3</td></tr> <tr><td>Network</td><td></td><td>230 V single-phase</td></tr> <tr><td>AC system</td><td></td><td>TT-TN</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>230 V</td></tr> <tr><td>Max. AC operating voltage</td><td>Uc</td><td>255 Vac</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>335 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>440 Vac disconnection</td></tr> <tr><td>Follow current</td><td>If</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 μs impulses</td><td>In</td><td>3 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>6 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td><td>Uoc</td><td>6 kV</td></tr> <tr><td>Withstand on overvoltages IEEE C62.41.1</td><td></td><td>6 kV/6 kA</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level L/N @ In (8/20μs)</td><td>Up L/N</td><td>1.5 kV</td></tr> <tr><td>Protection level L/PE @ In (8/20μs)</td><td>Up L/PE</td><td>1.5 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>Iscsr</td><td>3 000 A</td></tr> </table>		SPD type		3	Network		230 V single-phase	AC system		TT-TN	Nominal line voltage	Un	230 V	Max. AC operating voltage	Uc	255 Vac	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection	Follow current	If	None	Nominal discharge current 15 x 8/20 μs impulses	In	3 kA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	6 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	6 kV	Withstand on overvoltages IEEE C62.41.1		6 kV/6 kA	Protection mode(s)		Common/Differential mode	Protection level L/N @ In (8/20μs)	Up L/N	1.5 kV	Protection level L/PE @ In (8/20μs)	Up L/PE	1.5 kV	Admissible short-circuit current	Iscsr	3 000 A
SPD type		3																																																
Network		230 V single-phase																																																
AC system		TT-TN																																																
Nominal line voltage	Un	230 V																																																
Max. AC operating voltage	Uc	255 Vac																																																
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																																
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac disconnection																																																
Follow current	If	None																																																
Nominal discharge current 15 x 8/20 μs impulses	In	3 kA																																																
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	6 kA																																																
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	6 kV																																																
Withstand on overvoltages IEEE C62.41.1		6 kV/6 kA																																																
Protection mode(s)		Common/Differential mode																																																
Protection level L/N @ In (8/20μs)	Up L/N	1.5 kV																																																
Protection level L/PE @ In (8/20μs)	Up L/PE	1.5 kV																																																
Admissible short-circuit current	Iscsr	3 000 A																																																
Mechanical Characteristics																																																		
<table border="1"> <tr><td>Technology</td><td>MOV+GDT</td></tr> <tr><td>Connection to Network</td><td>Wires</td></tr> <tr><td>Mounting</td><td>AC outlet or screw terminal</td></tr> <tr><td>Housing material</td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu -40/+85°C</td></tr> <tr><td>Protection rating</td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td>Disconnection from AC network</td></tr> <tr><td>Disconnection indicator</td><td>Buzzer ON</td></tr> <tr><td>Voltage/operating indicator</td><td>without</td></tr> <tr><td>Dimensions</td><td>See diagram</td></tr> <tr><td>Weight</td><td>0.02 kg</td></tr> </table>		Technology	MOV+GDT	Connection to Network	Wires	Mounting	AC outlet or screw terminal	Housing material	Thermoplastic UL94 V-0	Operating temperature	Tu -40/+85°C	Protection rating	IP20	Failsafe mode	Disconnection from AC network	Disconnection indicator	Buzzer ON	Voltage/operating indicator	without	Dimensions	See diagram	Weight	0.02 kg																											
Technology	MOV+GDT																																																	
Connection to Network	Wires																																																	
Mounting	AC outlet or screw terminal																																																	
Housing material	Thermoplastic UL94 V-0																																																	
Operating temperature	Tu -40/+85°C																																																	
Protection rating	IP20																																																	
Failsafe mode	Disconnection from AC network																																																	
Disconnection indicator	Buzzer ON																																																	
Voltage/operating indicator	without																																																	
Dimensions	See diagram																																																	
Weight	0.02 kg																																																	
Disconnectors																																																		
<table border="1"> <tr><td>Thermal disconnector</td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td>Type 'S' or delayed</td></tr> </table>		Thermal disconnector	Internal	Installation ground fault breaker	Type 'S' or delayed																																													
Thermal disconnector	Internal																																																	
Installation ground fault breaker	Type 'S' or delayed																																																	
Standards																																																		
<table border="1"> <tr><td>Standards compliance</td><td>IEC 61643-11 / EN 61643-11 / UL1449 ed.5</td></tr> <tr><td>Certification</td><td></td></tr> </table>		Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5	Certification																																														
Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																	
Certification																																																		
Part number																																																		
561302																																																		

