



## Type 2 AC surge protector - 3-phase - Integrated fuses

# CITEL

### DACF25S-30-440



#### Type 2 AC surge protector

- ↳ In: 15 kA
- ↳ Imax: 25 kA
- ↳ Interne Disconnection device
- ↳ Pluggable module for each phase
- ↳ Remote signaling
- ↳ EN 61643-11, IEC 61643-11 and UL1449 ed.5 compliance



	<b>Electrical Characteristics</b>																																																												
	<table border="1"> <tr> <td>SPD type</td> <td colspan="2">2</td> </tr> <tr> <td>Network</td> <td colspan="2">230/400 V 3-phase</td> </tr> <tr> <td>AC system</td> <td colspan="2">IT</td> </tr> <tr> <td>Max. AC operating voltage</td> <td>Uc</td> <td>440 Vac</td> </tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td> <td>UT</td> <td>580 Vac withstand</td> </tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td> <td>UT</td> <td>770 Vac disconnection</td> </tr> <tr> <td>Residual Current Leakage current to Ground</td> <td>Ipe</td> <td>&lt; 1 mA</td> </tr> <tr> <td>Follow current</td> <td>If</td> <td>None</td> </tr> <tr> <td>Nominal discharge current 15 x 8/20 μs impulses</td> <td>In</td> <td>15 kA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>25 kA</td> </tr> <tr> <td>Total Maximum discharge current max. total withstand @ 8/20 μs</td> <td>Imax Total</td> <td>75 kA</td> </tr> <tr> <td>Connection mode(s)</td> <td colspan="2">L/PE</td> </tr> <tr> <td>Protection level L/PE @ In (8/20μs)</td> <td>Up L/PE</td> <td>2 kV</td> </tr> <tr> <td>Residual voltage L/PE at 5 kA @ 5 kA (8/20μs)</td> <td>Up-5kA</td> <td>1.5 kV</td> </tr> <tr> <td>Admissible short-circuit current</td> <td>Iscsr</td> <td>100 000 A</td> </tr> </table>	SPD type	2		Network	230/400 V 3-phase		AC system	IT		Max. AC operating voltage	Uc	440 Vac	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	580 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	770 Vac disconnection	Residual Current Leakage current to Ground	Ipe	< 1 mA	Follow current	If	None	Nominal discharge current 15 x 8/20 μs impulses	In	15 kA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	25 kA	Total Maximum discharge current max. total withstand @ 8/20 μs	Imax Total	75 kA	Connection mode(s)	L/PE		Protection level L/PE @ In (8/20μs)	Up L/PE	2 kV	Residual voltage L/PE at 5 kA @ 5 kA (8/20μs)	Up-5kA	1.5 kV	Admissible short-circuit current	Iscsr	100 000 A															
SPD type	2																																																												
Network	230/400 V 3-phase																																																												
AC system	IT																																																												
Max. AC operating voltage	Uc	440 Vac																																																											
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	580 Vac withstand																																																											
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	770 Vac disconnection																																																											
Residual Current Leakage current to Ground	Ipe	< 1 mA																																																											
Follow current	If	None																																																											
Nominal discharge current 15 x 8/20 μs impulses	In	15 kA																																																											
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	25 kA																																																											
Total Maximum discharge current max. total withstand @ 8/20 μs	Imax Total	75 kA																																																											
Connection mode(s)	L/PE																																																												
Protection level L/PE @ In (8/20μs)	Up L/PE	2 kV																																																											
Residual voltage L/PE at 5 kA @ 5 kA (8/20μs)	Up-5kA	1.5 kV																																																											
Admissible short-circuit current	Iscsr	100 000 A																																																											
<p>V: High-energy varistor  Ft: Thermal fuse  F: Overcurrent protection (fuse)  t*: Thermal disconnection system  C: Remote signal contact  MI: Disconnection indicator</p>	<b>Mechanical Characteristics</b> <table border="1"> <tr> <td>Technology</td> <td colspan="2">MOV</td> </tr> <tr> <td>SPD configuration</td> <td colspan="2">3-phase</td> </tr> <tr> <td>Connection to Network</td> <td colspan="2">By screw terminals: 2.5-25mm<sup>2</sup> (35mm<sup>2</sup> rigid)</td> </tr> <tr> <td>Format</td> <td colspan="2">Plug-in modular box</td> </tr> <tr> <td>Mounting</td> <td colspan="2">Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td colspan="2">Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td colspan="2">IP20</td> </tr> <tr> <td>Failsafe mode</td> <td colspan="2">Disconnection from AC network</td> </tr> <tr> <td>Disconnection indicator</td> <td colspan="2">1 mechanical indicator by pole - Red/Green</td> </tr> <tr> <td>Spare module(s)</td> <td colspan="2">MDACF25-440</td> </tr> <tr> <td>Remote signaling of disconnection</td> <td colspan="2">Output on changeover contact</td> </tr> <tr> <td>Wiring for remote signaling</td> <td colspan="2">1.5 mm<sup>2</sup> max.</td> </tr> <tr> <td>Max. Voltage/Current for remote signaling</td> <td colspan="2">250 V / 0.5 A (AC) / 30 V / 3 A (DC)</td> </tr> <tr> <td>Dimensions</td> <td colspan="2">See diagram - 3 TE (EN43880)</td> </tr> <tr> <td>Weight</td> <td colspan="2">0.317 kg</td> </tr> </table> <b>Disconnectors</b> <table border="1"> <tr> <td>Thermal disconnector</td> <td colspan="2">Internal</td> </tr> <tr> <td>Installation ground fault breaker</td> <td colspan="2">Type 'S' or delayed</td> </tr> <tr> <td>Back-up protection device</td> <td colspan="2">internal (equivalent AC rating : 40 A, gG Type)</td> </tr> </table> <b>Standards</b> <table border="1"> <tr> <td>Standards compliance</td> <td colspan="2">IEC 61643-11 / EN 61643-11 / UL1449 ed.5</td> </tr> </table> <b>Part number</b> <p>821410423</p>	Technology	MOV		SPD configuration	3-phase		Connection to Network	By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> rigid)		Format	Plug-in modular box		Mounting	Symmetrical rail 35 mm (EN 60715)		Housing material	Thermoplastic UL94 V-0		Operating temperature	Tu	-40/+85°C	Protection rating	IP20		Failsafe mode	Disconnection from AC network		Disconnection indicator	1 mechanical indicator by pole - Red/Green		Spare module(s)	MDACF25-440		Remote signaling of disconnection	Output on changeover contact		Wiring for remote signaling	1.5 mm <sup>2</sup> max.		Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)		Dimensions	See diagram - 3 TE (EN43880)		Weight	0.317 kg		Thermal disconnector	Internal		Installation ground fault breaker	Type 'S' or delayed		Back-up protection device	internal (equivalent AC rating : 40 A, gG Type)		Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5	
Technology	MOV																																																												
SPD configuration	3-phase																																																												
Connection to Network	By screw terminals: 2.5-25mm <sup>2</sup> (35mm <sup>2</sup> rigid)																																																												
Format	Plug-in modular box																																																												
Mounting	Symmetrical rail 35 mm (EN 60715)																																																												
Housing material	Thermoplastic UL94 V-0																																																												
Operating temperature	Tu	-40/+85°C																																																											
Protection rating	IP20																																																												
Failsafe mode	Disconnection from AC network																																																												
Disconnection indicator	1 mechanical indicator by pole - Red/Green																																																												
Spare module(s)	MDACF25-440																																																												
Remote signaling of disconnection	Output on changeover contact																																																												
Wiring for remote signaling	1.5 mm <sup>2</sup> max.																																																												
Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)																																																												
Dimensions	See diagram - 3 TE (EN43880)																																																												
Weight	0.317 kg																																																												
Thermal disconnector	Internal																																																												
Installation ground fault breaker	Type 'S' or delayed																																																												
Back-up protection device	internal (equivalent AC rating : 40 A, gG Type)																																																												
Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																												

