



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	Electrical Characteristics																																								
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RTC, ADSL2, VDSL2</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>150 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>170 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 10 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>I_{max}</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection level @ I_n (8/20 μs)</td> <td>Up L/L</td> <td>220 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>< 50 pF</td> </tr> <tr> <td>Impulse current 2 x 10/350 μs Test - D1 Category</td> <td>I_{imp}</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>I_n</td> <td>5 kA</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>< 4.7 Ohm</td> </tr> </table>		Network		RTC, ADSL2, VDSL2	Nominal line voltage	Un	150 V	Max. DC operating voltage	Uc	170 Vdc	Max. frequency	f max.	> 10 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA	Line inductance		No	Protection level @ I _n (8/20 μs)	Up L/L	220 V	Max. capacitance	C	< 50 pF	Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	5 kA	Nominal discharge current C2 Category	I _n	5 kA	Line resistance		< 4.7 Ohm
Network		RTC, ADSL2, VDSL2																																							
Nominal line voltage	Un	150 V																																							
Max. DC operating voltage	Uc	170 Vdc																																							
Max. frequency	f max.	> 10 MHz																																							
Insertion loss		< 1 dB																																							
Max. load current @25°C	IL	300 mA																																							
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA																																							
Line inductance		No																																							
Protection level @ I _n (8/20 μs)	Up L/L	220 V																																							
Max. capacitance	C	< 50 pF																																							
Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	5 kA																																							
Nominal discharge current C2 Category	I _n	5 kA																																							
Line resistance		< 4.7 Ohm																																							
Mechanical Characteristics																																									
Technology		GDT+Clamping diode																																							
SPD configuration		1-pair+shielded																																							
Connection to Network		Spring terminal: cross section 0.5-2.5mm ²																																							
Mounting		Symmetrical rail 35 mm (EN 60715)																																							
Housing material		Thermoplastic UL94 V-0																																							
Operating and storage temperature		-40/+85°C																																							
Protection rating		IP20																																							
Fail-safe mode		Short-circuit																																							
Disconnection indicator		Transmission interrupt - default mode 2																																							
Spare module(s)		DLAM-170																																							
Standards																																									
Standards compliance		IEC 61643-21 / EN 61643-21																																							
Part number																																									
6401054																																									

