



CITEL

1-pair DIN rail plug-in Data surge protector

DLA-48DBC/R



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Plug-out with line cut-off
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	Electrical Characteristics																																								
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td colspan="2">Fipway, WorldFIP, FieldBus-h2</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>48 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>53 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 20 MHz</td> </tr> <tr> <td>Insertion loss</td> <td colspan="2">< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>I_{max}</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td colspan="2">No</td> </tr> <tr> <td>Protection level @ I_n (8/20 μs)</td> <td>Up L/L</td> <td>75 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>< 50 pF</td> </tr> <tr> <td>Impulse current 2 x 10/350 μs Test - D1 Category</td> <td>I_{imp}</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>I_n</td> <td>5 kA</td> </tr> <tr> <td>Line resistance</td> <td colspan="2">< 4.7 Ohm</td> </tr> </table>		Network	Fipway, WorldFIP, FieldBus-h2		Nominal line voltage	Un	48 V	Max. DC operating voltage	Uc	53 Vdc	Max. frequency	f max.	> 20 MHz	Insertion loss	< 1 dB		Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA	Line inductance	No		Protection level @ I _n (8/20 μs)	Up L/L	75 V	Max. capacitance	C	< 50 pF	Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	5 kA	Nominal discharge current C2 Category	I _n	5 kA	Line resistance	< 4.7 Ohm	
Network	Fipway, WorldFIP, FieldBus-h2																																								
Nominal line voltage	Un	48 V																																							
Max. DC operating voltage	Uc	53 Vdc																																							
Max. frequency	f max.	> 20 MHz																																							
Insertion loss	< 1 dB																																								
Max. load current @25°C	IL	300 mA																																							
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	20 kA																																							
Line inductance	No																																								
Protection level @ I _n (8/20 μs)	Up L/L	75 V																																							
Max. capacitance	C	< 50 pF																																							
Impulse current 2 x 10/350 μs Test - D1 Category	I _{imp}	5 kA																																							
Nominal discharge current C2 Category	I _n	5 kA																																							
Line resistance	< 4.7 Ohm																																								
Mechanical Characteristics																																									
<table border="1"> <tr> <td>Technology</td> <td colspan="2">GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td colspan="2">1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td colspan="2">Spring terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Format</td> <td colspan="2">Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td colspan="2">Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td colspan="2">Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating and storage temperature</td> <td colspan="2">-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td colspan="2">IP20</td> </tr> <tr> <td>Failsafe mode</td> <td colspan="2">Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td colspan="2">Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td colspan="2">DLAM-48dBC</td> </tr> <tr> <td>Dimensions</td> <td colspan="2">See diagram</td> </tr> <tr> <td>Weight</td> <td colspan="2">0.065 kg</td> </tr> </table>			Technology	GDT+Clamping diode		SPD configuration	1-pair+shielded		Connection to Network	Spring terminal: cross section 0.5-2.5mm ²		Format	Plug-in DIN box		Mounting	Symmetrical rail 35 mm (EN 60715)		Housing material	Thermoplastic UL94 V-0		Operating and storage temperature	-40/+85°C		Protection rating	IP20		Failsafe mode	Short-circuit		Disconnection indicator	Transmission interrupt - default mode 2		Spare module(s)	DLAM-48dBC		Dimensions	See diagram		Weight	0.065 kg	
Technology	GDT+Clamping diode																																								
SPD configuration	1-pair+shielded																																								
Connection to Network	Spring terminal: cross section 0.5-2.5mm ²																																								
Format	Plug-in DIN box																																								
Mounting	Symmetrical rail 35 mm (EN 60715)																																								
Housing material	Thermoplastic UL94 V-0																																								
Operating and storage temperature	-40/+85°C																																								
Protection rating	IP20																																								
Failsafe mode	Short-circuit																																								
Disconnection indicator	Transmission interrupt - default mode 2																																								
Spare module(s)	DLAM-48dBC																																								
Dimensions	See diagram																																								
Weight	0.065 kg																																								
Standards																																									
Standards compliance IEC 61643-21 / EN 61643-21																																									
Part number																																									
6404214																																									

