



Surge protector for LED lighting system Class 1

CITEL

MLPC-VG1-230L-R



- Type 2 (or 3) surge protectors for LED
- Class 1
- Very compact
- Plate mounting
- Spring terminal connection
- Status indicator
- Disconnection AC end of life
- EN 61643-11 compliance



	Electrical Characteristics																																																							
<p>V: Varistor GSG: Specific gas tube LED: Disconnection indicator Ft: Thermal fuse t*: Thermal system disconnection</p>	<table border="1"> <tr> <td>SPD type</td> <td></td> <td>2+3</td> </tr> <tr> <td>Network</td> <td></td> <td>220-240 V Single-phase</td> </tr> <tr> <td>AC system</td> <td></td> <td>TT-TN</td> </tr> <tr> <td>Max. AC operating voltage</td> <td>Uc</td> <td>320 Vac</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>10 A</td> </tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td> <td>UT</td> <td>335 Vac withstand</td> </tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td> <td>UT</td> <td>440 Vac withstand</td> </tr> <tr> <td>Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection</td> <td>UT</td> <td>1200 V/300A/200 ms disconnection</td> </tr> <tr> <td>Residual Current Leakage current to Ground</td> <td>Ipe</td> <td>None</td> </tr> <tr> <td>Nominal discharge current 15 x 8/20 μs impulses</td> <td>In</td> <td>5 kA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>10 kA</td> </tr> <tr> <td>Total Maximum discharge current max. total withstand @ 8/20 μs</td> <td>Imax Total</td> <td>20 kA</td> </tr> <tr> <td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td> <td>Uoc</td> <td>10 kV</td> </tr> <tr> <td>Withstand on overvoltages IEEE C62.41.1</td> <td></td> <td>10 kV</td> </tr> <tr> <td>Protection mode(s)</td> <td></td> <td>Common/Differential mode</td> </tr> <tr> <td>Protection level L/N @ In (8/20μs)</td> <td>Up L/N</td> <td>1.5 kV</td> </tr> <tr> <td>Protection level L/PE @ In (8/20μs)</td> <td>Up L/PE</td> <td>1.5 kV</td> </tr> <tr> <td>Admissible short-circuit current</td> <td>Iscsr</td> <td>10 000 A</td> </tr> </table>		SPD type		2+3	Network		220-240 V Single-phase	AC system		TT-TN	Max. AC operating voltage	Uc	320 Vac	Max. load current @25°C	IL	10 A	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac withstand	Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection	UT	1200 V/300A/200 ms disconnection	Residual Current Leakage current to Ground	Ipe	None	Nominal discharge current 15 x 8/20 μs impulses	In	5 kA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	10 kA	Total Maximum discharge current max. total withstand @ 8/20 μs	Imax Total	20 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	10 kV	Withstand on overvoltages IEEE C62.41.1		10 kV	Protection mode(s)		Common/Differential mode	Protection level L/N @ In (8/20μs)	Up L/N	1.5 kV	Protection level L/PE @ In (8/20μs)	Up L/PE	1.5 kV	Admissible short-circuit current	Iscsr	10 000 A
SPD type		2+3																																																						
Network		220-240 V Single-phase																																																						
AC system		TT-TN																																																						
Max. AC operating voltage	Uc	320 Vac																																																						
Max. load current @25°C	IL	10 A																																																						
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	335 Vac withstand																																																						
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	440 Vac withstand																																																						
Temporary Over Voltage N/PE (TOV HT) Without disconnection or with safety disconnection	UT	1200 V/300A/200 ms disconnection																																																						
Residual Current Leakage current to Ground	Ipe	None																																																						
Nominal discharge current 15 x 8/20 μs impulses	In	5 kA																																																						
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	10 kA																																																						
Total Maximum discharge current max. total withstand @ 8/20 μs	Imax Total	20 kA																																																						
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	10 kV																																																						
Withstand on overvoltages IEEE C62.41.1		10 kV																																																						
Protection mode(s)		Common/Differential mode																																																						
Protection level L/N @ In (8/20μs)	Up L/N	1.5 kV																																																						
Protection level L/PE @ In (8/20μs)	Up L/PE	1.5 kV																																																						
Admissible short-circuit current	Iscsr	10 000 A																																																						
	Mechanical Characteristics																																																							
	<table border="1"> <tr> <td>Technology</td> <td></td> <td>VG Technology (MOV+GSG)</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By spring - max. cross section 1.5mm²</td> </tr> <tr> <td>Mounting</td> <td></td> <td>On plate</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Disconnection and AC line cut-off</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>LED green OFF and AC network cut-off</td> </tr> <tr> <td>Voltage/operating indicator</td> <td></td> <td>Green Led ON</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> <tr> <td>Weight</td> <td></td> <td>0.036 kg</td> </tr> </table>		Technology		VG Technology (MOV+GSG)	Connection to Network		By spring - max. cross section 1.5mm ²	Mounting		On plate	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection and AC line cut-off	Disconnection indicator		LED green OFF and AC network cut-off	Voltage/operating indicator		Green Led ON	Dimensions		See diagram	Weight		0.036 kg																					
Technology		VG Technology (MOV+GSG)																																																						
Connection to Network		By spring - max. cross section 1.5mm ²																																																						
Mounting		On plate																																																						
Housing material		Thermoplastic UL94 V-0																																																						
Operating temperature	Tu	-40/+85°C																																																						
Protection rating		IP20																																																						
Failsafe mode		Disconnection and AC line cut-off																																																						
Disconnection indicator		LED green OFF and AC network cut-off																																																						
Voltage/operating indicator		Green Led ON																																																						
Dimensions		See diagram																																																						
Weight		0.036 kg																																																						
	Disconnectors																																																							
	<table border="1"> <tr> <td>Thermal disconnector</td> <td></td> <td>Internal</td> </tr> <tr> <td>Installation ground fault breaker</td> <td></td> <td>Type 'S' or delayed</td> </tr> </table>		Thermal disconnector		Internal	Installation ground fault breaker		Type 'S' or delayed																																																
Thermal disconnector		Internal																																																						
Installation ground fault breaker		Type 'S' or delayed																																																						
	Standards																																																							
	<table border="1"> <tr> <td>Standards compliance</td> <td></td> <td>EN 61643-11 / IEC 61643-11</td> </tr> <tr> <td>Certification</td> <td></td> <td></td> </tr> </table>		Standards compliance		EN 61643-11 / IEC 61643-11	Certification																																																		
Standards compliance		EN 61643-11 / IEC 61643-11																																																						
Certification																																																								
	Part number																																																							
	836211																																																							

