


DDC30S-10-85



- Surge protector for DC supplies 1-pole
- Type 1 + 2
- In: 15 kA / I_{max}: 30 kA
- I_{imp}: 4kA
- Pluggable module
- Remote signaling
- prIEC 61643-41 compliance



Electrical Characteristics	
SPD type	1+2
Nominal DC voltage	Un-dc 75 Vdc
Max. AC operating voltage	Uc 60 Vac
Max. DC operating voltage	Uc 85 Vdc
Residual Current Leakage current to Ground	I _{pe} < 0.1 mA
Follow current	I _f None
Nominal discharge current 15 x 8/20 μs impulses	I _n 20 kA
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max} 30 kA
Impulse current by pole max. withstand 10/350 μs by pole	I _{imp} 4 kA
Connection mode(s)	+/-PE or -/PE
Protection level +/-PE (-/PE) @ I _n (8/20 μs)	U _p 390 V / -
Admissible short-circuit current	I _{sc} 50 000 A
Mechanical Characteristics	
Technology	MOV
SPD configuration	Single phase
Connection to Network	Srew terminals: 2.5-25mm ² +/- 1.5-10mm ²
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	T _u -40/+85°C
Protection rating	IP20
Failsafe mode	Disconnection from DC network
Disconnection indicator	1 mechanical indicator - Red/Green
Spare module(s)	MDDC30-85
Remote signaling of disconnection	Output on changeover contact
Dimensions	See diagram - 1TE (EN43880)
Weight	0.070 kg
Disconnectors	
Thermal disconnector	Internal
Back-up protection device	50 A min. - 125 A max. - Fuses Type gG
Standards	
Standards compliance	prIEC 61643-41
Part number	
828110221	