



2-pair monobloc Data surge protector

CITEL

DLU2-12D3



- For DIN rail mounting
- Monobloc housing
- 2-pair
- Un: 12 V
- IEC 61643-21 compliance
- UL497A



	Electrical Characteristics																																											
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>Profibus-FMS, Interbus, FieldBus-H1, Batibus, RS232, RS485</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>12 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>15 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection mode(s)</td> <td></td> <td>Common/Differential mode</td> </tr> <tr> <td>Protection level Following the test category C3 (IEC61643-21) - Line/Line</td> <td>Up</td> <td>30 V</td> </tr> <tr> <td>Max. capacitance</td> <td>C</td> <td>< 50 pF</td> </tr> <tr> <td>Impulse current 2 x 10/350μs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>In</td> <td>5 kA</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>< 4.7 Ohm</td> </tr> </table>		Network		Profibus-FMS, Interbus, FieldBus-H1, Batibus, RS232, RS485	Nominal line voltage	Un	12 V	Max. DC operating voltage	Uc	15 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance		No	Protection mode(s)		Common/Differential mode	Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	30 V	Max. capacitance	C	< 50 pF	Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA	Nominal discharge current C2 Category	In	5 kA	Line resistance		< 4.7 Ohm
Network		Profibus-FMS, Interbus, FieldBus-H1, Batibus, RS232, RS485																																										
Nominal line voltage	Un	12 V																																										
Max. DC operating voltage	Uc	15 Vdc																																										
Max. frequency	f max.	> 3 MHz																																										
Insertion loss		< 1 dB																																										
Max. load current @25°C	IL	300 mA																																										
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																										
Line inductance		No																																										
Protection mode(s)		Common/Differential mode																																										
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	30 V																																										
Max. capacitance	C	< 50 pF																																										
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA																																										
Nominal discharge current C2 Category	In	5 kA																																										
Line resistance		< 4.7 Ohm																																										
Mechanical Characteristics																																												
		Technology																																										
		SPD configuration																																										
		Connection to Network																																										
		Format																																										
		Mounting																																										
		Housing material																																										
		Operating temperature																																										
		Protection rating																																										
		Failsafe mode																																										
		Disconnection indicator																																										
		Remote signaling of disconnection																																										
		Dimensions																																										
		Weight																																										
Standards																																												
		Standards compliance																																										
		Certification																																										
Part number																																												
		640403																																										

