



1-pair DIN rail plug-in Data surge protector

CITEL

DLAS1-48D3



- › 1-pair Pluggable SPD for dataline
- › Visual indicator in failsafe behaviour
- › Without line cut-off
- › Line voltage 48 Vdc
- › Din rail mounting, Screw terminals
- › IEC/EN 61643-21 and UL497A compliance



	Electrical Characteristics																																					
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube PTC: Thermal resistor R: Resistor D : Clamping diode Vi : Indicator</p>	<table border="1"> <tr><td>Network</td><td></td><td>RNIS-T0, 48 V line</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>48 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>53 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 3 MHz</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>300 mA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 µs by pole</td><td>Imax</td><td>20 kA</td></tr> <tr><td>Line inductance</td><td></td><td>No</td></tr> <tr><td>Protection level @ In (8/20 µs)</td><td>Up L/L</td><td>70 V</td></tr> <tr><td>Impulse current 2 x 10/350µs Test - D1 Category</td><td>limp</td><td>5 kA</td></tr> <tr><td>Line/Line Nominal discharge current C2 Category</td><td>In L/L</td><td>5 kA</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category</td><td>In L/PE</td><td>5 kA</td></tr> <tr><td>Line resistance</td><td></td><td>< 4.7 Ohm</td></tr> </table>		Network		RNIS-T0, 48 V line	Nominal line voltage	Un	48 V	Max. DC operating voltage	Uc	53 Vdc	Max. frequency	f max.	> 3 MHz	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA	Line inductance		No	Protection level @ In (8/20 µs)	Up L/L	70 V	Impulse current 2 x 10/350µs Test - D1 Category	limp	5 kA	Line/Line Nominal discharge current C2 Category	In L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	5 kA	Line resistance		< 4.7 Ohm
Network		RNIS-T0, 48 V line																																				
Nominal line voltage	Un	48 V																																				
Max. DC operating voltage	Uc	53 Vdc																																				
Max. frequency	f max.	> 3 MHz																																				
Max. load current @25°C	IL	300 mA																																				
Max. discharge current max. withstand @ 8/20 µs by pole	Imax	20 kA																																				
Line inductance		No																																				
Protection level @ In (8/20 µs)	Up L/L	70 V																																				
Impulse current 2 x 10/350µs Test - D1 Category	limp	5 kA																																				
Line/Line Nominal discharge current C2 Category	In L/L	5 kA																																				
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	In L/PE	5 kA																																				
Line resistance		< 4.7 Ohm																																				
	Mechanical Characteristics																																					
	<table border="1"> <tr><td>Technology</td><td></td><td>GDT+Clamping diode+PTC (thermal resistor) + Resistor</td></tr> <tr><td>SPD configuration</td><td></td><td>1-pair+shielded</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminal: cross section 0.5-2.5mm²</td></tr> <tr><td>Format</td><td></td><td>Plug-in DIN box</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Opening line - transmission cut-off - fault mode 2</td></tr> <tr><td>Disconnection indicator</td><td></td><td>Visual indicator is red</td></tr> <tr><td>Spare module(s)</td><td></td><td>DLAS1M-48D3</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> </table>		Technology		GDT+Clamping diode+PTC (thermal resistor) + Resistor	SPD configuration		1-pair+shielded	Connection to Network		By screw terminal: cross section 0.5-2.5mm ²	Format		Plug-in DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Opening line - transmission cut-off - fault mode 2	Disconnection indicator		Visual indicator is red	Spare module(s)		DLAS1M-48D3	Dimensions		See diagram
Technology		GDT+Clamping diode+PTC (thermal resistor) + Resistor																																				
SPD configuration		1-pair+shielded																																				
Connection to Network		By screw terminal: cross section 0.5-2.5mm ²																																				
Format		Plug-in DIN box																																				
Mounting		Symmetrical rail 35 mm (EN 60715)																																				
Housing material		Thermoplastic UL94 V-0																																				
Operating temperature	Tu	-40/+85°C																																				
Protection rating		IP20																																				
Failsafe mode		Opening line - transmission cut-off - fault mode 2																																				
Disconnection indicator		Visual indicator is red																																				
Spare module(s)		DLAS1M-48D3																																				
Dimensions		See diagram																																				
	Standards																																					
	Standards compliance IEC 61643-21 / EN 61643-21 / UL497A																																					
	Part number 6415041																																					

