



1-pair DIN rail plug-in Data surge protector

CITEL

DLAWS1-48D3



- 1-pair Surge protection
- Pluggable protection module
- Optical fault indication
- Indirect shield connection
- Visual indicator in failsafe behaviour
- Indirect earthing
- Current circuit disconnection when module is unplugged
- Conforms to IEC 61643-21, VDE 0845-3-1 and UL497B



	Electrical Characteristics																																											
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube PTC: Thermal resistor R: Resistor D : Clamping diode Vi : Indicator</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RNIS-T0, 48 V line</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>48 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>53 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. discharge current <i>max. withstand @ 8/20 μs by pole</i></td> <td>I_{max}</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection mode(s)</td> <td></td> <td>Common/Differential mode</td> </tr> <tr> <td>Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i></td> <td>Up</td> <td>70 V</td> </tr> <tr> <td>Impulse current <i>2 x 10/350μs Test - D1 Category</i></td> <td>I_{imp}</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current <i>C2 Category</i></td> <td>I_n</td> <td>5 kA</td> </tr> <tr> <td>Line/Line Nominal discharge current <i>C2 Category</i></td> <td>I_{n L/L}</td> <td>5 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) <i>8/20μs Test x 10 - C2 Category</i></td> <td>I_{n L/PE}</td> <td>5 kA</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>< 4.7 Ohm</td> </tr> </table>		Network		RNIS-T0, 48 V line	Nominal line voltage	Un	48 V	Max. DC operating voltage	Uc	53 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max}	20 kA	Line inductance		No	Protection mode(s)		Common/Differential mode	Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i>	Up	70 V	Impulse current <i>2 x 10/350μs Test - D1 Category</i>	I _{imp}	5 kA	Nominal discharge current <i>C2 Category</i>	I _n	5 kA	Line/Line Nominal discharge current <i>C2 Category</i>	I _{n L/L}	5 kA	Nominal Discharge Current, X-C (Line/Earth) <i>8/20μs Test x 10 - C2 Category</i>	I _{n L/PE}	5 kA	Line resistance		< 4.7 Ohm
Network		RNIS-T0, 48 V line																																										
Nominal line voltage	Un	48 V																																										
Max. DC operating voltage	Uc	53 Vdc																																										
Max. frequency	f max.	> 3 MHz																																										
Insertion loss		< 1 dB																																										
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max}	20 kA																																										
Line inductance		No																																										
Protection mode(s)		Common/Differential mode																																										
Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i>	Up	70 V																																										
Impulse current <i>2 x 10/350μs Test - D1 Category</i>	I _{imp}	5 kA																																										
Nominal discharge current <i>C2 Category</i>	I _n	5 kA																																										
Line/Line Nominal discharge current <i>C2 Category</i>	I _{n L/L}	5 kA																																										
Nominal Discharge Current, X-C (Line/Earth) <i>8/20μs Test x 10 - C2 Category</i>	I _{n L/PE}	5 kA																																										
Line resistance		< 4.7 Ohm																																										
<p>Connection ribbons available:</p> <table border="1"> <thead> <tr> <th>Nb of pole</th> <th>Ref. Ribbon</th> </tr> </thead> <tbody> <tr> <td>2 - 5</td> <td>R-BUS 5P (301134)</td> </tr> <tr> <td>6 - 10</td> <td>R-BUS 10P (301133)</td> </tr> <tr> <td>11 - 25</td> <td>R-BUS 25P (301135)</td> </tr> <tr> <td>26 - 49</td> <td>R-BUS 49P (301143)</td> </tr> </tbody> </table>	Nb of pole	Ref. Ribbon	2 - 5	R-BUS 5P (301134)	6 - 10	R-BUS 10P (301133)	11 - 25	R-BUS 25P (301135)	26 - 49	R-BUS 49P (301143)	Mechanical Characteristics																																	
Nb of pole	Ref. Ribbon																																											
2 - 5	R-BUS 5P (301134)																																											
6 - 10	R-BUS 10P (301133)																																											
11 - 25	R-BUS 25P (301135)																																											
26 - 49	R-BUS 49P (301143)																																											
Standards																																												
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497A																																										
Part number																																												
6419041																																												

