



1-pair DIN rail plug-in Data surge protector

CITEL

DLAS1-06D3



- 1-pair Pluggable SPD for dataline
- Visual indicator in failsafe behaviour
- Without line cut-off
- Line voltage 6 Vdc
- Din rail mounting, Screw terminals
- IEC/EN 61643-21 and UL497A compliance



	Electrical Characteristics																																					
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube PTC: Thermal resistor R: Resistor D : Clamping diode Vi : Indicator</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RS422</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>6 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>8 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection level @ In (8/20 μs)</td> <td>Up L/L</td> <td>20 V</td> </tr> <tr> <td>Impulse current 2 x 10/350μs Test - D1 Category</td> <td>Iimp</td> <td>5 kA</td> </tr> <tr> <td>Line/Line Nominal discharge current C2 Category</td> <td>In L/L</td> <td>5 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category</td> <td>In L/PE</td> <td>5 kA</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>< 4.7 Ohm</td> </tr> </table>		Network		RS422	Nominal line voltage	Un	6 V	Max. DC operating voltage	Uc	8 Vdc	Max. frequency	f max.	> 3 MHz	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance		No	Protection level @ In (8/20 μs)	Up L/L	20 V	Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA	Line/Line Nominal discharge current C2 Category	In L/L	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	In L/PE	5 kA	Line resistance		< 4.7 Ohm
Network		RS422																																				
Nominal line voltage	Un	6 V																																				
Max. DC operating voltage	Uc	8 Vdc																																				
Max. frequency	f max.	> 3 MHz																																				
Max. load current @25°C	IL	300 mA																																				
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																				
Line inductance		No																																				
Protection level @ In (8/20 μs)	Up L/L	20 V																																				
Impulse current 2 x 10/350μs Test - D1 Category	Iimp	5 kA																																				
Line/Line Nominal discharge current C2 Category	In L/L	5 kA																																				
Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	In L/PE	5 kA																																				
Line resistance		< 4.7 Ohm																																				
ELEC																																						
	<table border="1"> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>24 V</td> </tr> </table>		Nominal line voltage	Un	24 V																																	
Nominal line voltage	Un	24 V																																				
Mechanical Characteristics																																						
<table border="1"> <tr> <td>Technology</td> <td colspan="2">GDT+Clamping diode+PTC (thermal resistor) + Resistor</td> </tr> <tr> <td>SPD configuration</td> <td colspan="2">1-pair+shielded</td> </tr> <tr> <td>Connection to Network</td> <td colspan="2">By screw terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Format</td> <td colspan="2">Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td colspan="2">Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td colspan="2">Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td colspan="2">IP20</td> </tr> <tr> <td>Failsafe mode</td> <td colspan="2">Opening line - transmission cut-off - fault mode 2</td> </tr> <tr> <td>Disconnection indicator</td> <td colspan="2">Visual indicator is red</td> </tr> <tr> <td>Spare module(s)</td> <td colspan="2">DLAS1M-06D3</td> </tr> <tr> <td>Dimensions</td> <td colspan="2">See diagram</td> </tr> </table>			Technology	GDT+Clamping diode+PTC (thermal resistor) + Resistor		SPD configuration	1-pair+shielded		Connection to Network	By screw terminal: cross section 0.5-2.5mm ²		Format	Plug-in DIN box		Mounting	Symmetrical rail 35 mm (EN 60715)		Housing material	Thermoplastic UL94 V-0		Operating temperature	Tu	-40/+85°C	Protection rating	IP20		Failsafe mode	Opening line - transmission cut-off - fault mode 2		Disconnection indicator	Visual indicator is red		Spare module(s)	DLAS1M-06D3		Dimensions	See diagram	
Technology	GDT+Clamping diode+PTC (thermal resistor) + Resistor																																					
SPD configuration	1-pair+shielded																																					
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²																																					
Format	Plug-in DIN box																																					
Mounting	Symmetrical rail 35 mm (EN 60715)																																					
Housing material	Thermoplastic UL94 V-0																																					
Operating temperature	Tu	-40/+85°C																																				
Protection rating	IP20																																					
Failsafe mode	Opening line - transmission cut-off - fault mode 2																																					
Disconnection indicator	Visual indicator is red																																					
Spare module(s)	DLAS1M-06D3																																					
Dimensions	See diagram																																					
Standards																																						
<table border="1"> <tr> <td>Standards compliance</td> <td colspan="2">IEC 61643-21 / EN 61643-21 / UL497A</td> </tr> </table>			Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A																																		
Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A																																					
<table border="1"> <tr> <td>Certification</td> <td colspan="2">SIL</td> </tr> </table>			Certification	SIL																																		
Certification	SIL																																					
<table border="1"> <tr> <td>Part number</td> <td colspan="2">6415011</td> </tr> </table>			Part number	6415011																																		
Part number	6415011																																					

