



Type 2 PV Surge Protector for PCB mounting

CITEL

PPV25S-10-300



- Type 2 surge protector for Photovoltaic
- PCB mounting
- I_{max}: 25 kA
- Remote signaling
- EN 50539-11 and IEC 61643-31 compliance*



	Electrical Characteristics																																																	
<p>V: High-energy varistor Ft: Thermal fuse C: Remote signal contact t°: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>2</td></tr> <tr><td>Nominal PV voltage</td><td>Uocstc</td><td>600 Vdc</td></tr> <tr><td>Max. PV operating voltage</td><td>Ucpv</td><td>300 Vdc</td></tr> <tr><td>Max. PV operating voltage (star mounting)</td><td>Ucpv</td><td>600 Vdc</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>Ipe</td><td>None</td></tr> <tr><td>PV Permanent Operating current Current consumption at Ucpv</td><td>Icpv</td><td>< 0.1 mA</td></tr> <tr><td>Follow current</td><td>If</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 μs impulses</td><td>In</td><td>10 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>I_{max}</td><td>25 kA</td></tr> <tr><td>Current withstand short circuit PV</td><td>Iscpv</td><td>15 000 A</td></tr> <tr><td>Connection mode(s)</td><td></td><td>+/-PE</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level @ In (8/20μs)</td><td>Up</td><td>1.1 kV</td></tr> <tr><td>Protection level (star mounting) (+/-) / (+/PE or -/PE) @ In (8/20μs)</td><td>Up</td><td>2.2 kV</td></tr> <tr><td>Protection level +/- @ In (8/20μs)</td><td>Up</td><td>5.1 kV</td></tr> <tr><td>Protection level +/PE (-/PE) @ In (8/20μs)</td><td>Up</td><td>2.5 kV</td></tr> </table>		SPD type		2	Nominal PV voltage	Uocstc	600 Vdc	Max. PV operating voltage	Ucpv	300 Vdc	Max. PV operating voltage (star mounting)	Ucpv	600 Vdc	Residual Current Leakage current to Ground	Ipe	None	PV Permanent Operating current Current consumption at Ucpv	Icpv	< 0.1 mA	Follow current	If	None	Nominal discharge current 15 x 8/20 μs impulses	In	10 kA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	25 kA	Current withstand short circuit PV	Iscpv	15 000 A	Connection mode(s)		+/-PE	Protection mode(s)		Common/Differential mode	Protection level @ In (8/20μs)	Up	1.1 kV	Protection level (star mounting) (+/-) / (+/PE or -/PE) @ In (8/20μs)	Up	2.2 kV	Protection level +/- @ In (8/20μs)	Up	5.1 kV	Protection level +/PE (-/PE) @ In (8/20μs)	Up	2.5 kV
SPD type		2																																																
Nominal PV voltage	Uocstc	600 Vdc																																																
Max. PV operating voltage	Ucpv	300 Vdc																																																
Max. PV operating voltage (star mounting)	Ucpv	600 Vdc																																																
Residual Current Leakage current to Ground	Ipe	None																																																
PV Permanent Operating current Current consumption at Ucpv	Icpv	< 0.1 mA																																																
Follow current	If	None																																																
Nominal discharge current 15 x 8/20 μs impulses	In	10 kA																																																
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	25 kA																																																
Current withstand short circuit PV	Iscpv	15 000 A																																																
Connection mode(s)		+/-PE																																																
Protection mode(s)		Common/Differential mode																																																
Protection level @ In (8/20μs)	Up	1.1 kV																																																
Protection level (star mounting) (+/-) / (+/PE or -/PE) @ In (8/20μs)	Up	2.2 kV																																																
Protection level +/- @ In (8/20μs)	Up	5.1 kV																																																
Protection level +/PE (-/PE) @ In (8/20μs)	Up	2.5 kV																																																
	Mechanical Characteristics																																																	
	<table border="1"> <tr><td>Technology</td><td></td><td>MOV</td></tr> <tr><td>Connection to Network</td><td></td><td>Through soldering pins</td></tr> <tr><td>Format</td><td></td><td>Plug-in modular box</td></tr> <tr><td>Mounting</td><td></td><td>On Printed Circuit Board</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Disconnection SPD of the PV line</td></tr> <tr><td>Disconnection indicator</td><td></td><td>1 mechanical indicator</td></tr> <tr><td>Spare module(s)</td><td></td><td>DSM50PV-600</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>Output on changeover contact</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> <tr><td>Weight</td><td></td><td>0.025 kg</td></tr> <tr><td>Weight</td><td></td><td>0.051 kg</td></tr> </table>		Technology		MOV	Connection to Network		Through soldering pins	Format		Plug-in modular box	Mounting		On Printed Circuit Board	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection SPD of the PV line	Disconnection indicator		1 mechanical indicator	Spare module(s)		DSM50PV-600	Remote signaling of disconnection		Output on changeover contact	Dimensions		See diagram	Weight		0.025 kg	Weight		0.051 kg						
Technology		MOV																																																
Connection to Network		Through soldering pins																																																
Format		Plug-in modular box																																																
Mounting		On Printed Circuit Board																																																
Housing material		Thermoplastic UL94 V-0																																																
Operating temperature	Tu	-40/+85°C																																																
Protection rating		IP20																																																
Failsafe mode		Disconnection SPD of the PV line																																																
Disconnection indicator		1 mechanical indicator																																																
Spare module(s)		DSM50PV-600																																																
Remote signaling of disconnection		Output on changeover contact																																																
Dimensions		See diagram																																																
Weight		0.025 kg																																																
Weight		0.051 kg																																																
	Disconnectors																																																	
	<table border="1"> <tr><td>Thermal disconnector</td><td></td><td>Internal</td></tr> <tr><td>Back-up protection device</td><td></td><td>Without</td></tr> </table>		Thermal disconnector		Internal	Back-up protection device		Without																																										
Thermal disconnector		Internal																																																
Back-up protection device		Without																																																
	Standards																																																	
	<table border="1"> <tr><td>Standards compliance</td><td></td><td>IEC 61643-31 / EN 50539-11 *The standard cover devices. PPV /PAC series are components. Compliant when combined is an assembly.</td></tr> </table>		Standards compliance		IEC 61643-31 / EN 50539-11 *The standard cover devices. PPV /PAC series are components. Compliant when combined is an assembly.																																													
Standards compliance		IEC 61643-31 / EN 50539-11 *The standard cover devices. PPV /PAC series are components. Compliant when combined is an assembly.																																																
	Part number																																																	
	8721210																																																	

