



Type 2+3 AC surge protector -3-pole - Monobloc

CITEL

DACN30VGS-30-1260



- Type 2 + 3 AC surge protector
- VG Technology
- In: 15 kA
- No leakage current
- Monobloc module for each phase
- Remote signaling
- Optimized to TOV
- EN 61643-11, IEC 61643-11 and UL1449 ed.5 compliance



	<table border="1"> <thead> <tr> <th colspan="3">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>SPD type</td> <td></td> <td>2+3</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>1140 Vac</td> </tr> <tr> <td>Max. AC operating voltage</td> <td>Uc</td> <td>1260 Vac</td> </tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td> <td>UT</td> <td>1650 Vac withstand</td> </tr> <tr> <td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td> <td>UT</td> <td>2200 Vac disconnection</td> </tr> </tbody> </table>	Electrical Characteristics			SPD type		2+3	Nominal line voltage	Un	1140 Vac	Max. AC operating voltage	Uc	1260 Vac	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	1650 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	2200 Vac disconnection																																																						
Electrical Characteristics																																																																									
SPD type		2+3																																																																							
Nominal line voltage	Un	1140 Vac																																																																							
Max. AC operating voltage	Uc	1260 Vac																																																																							
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	1650 Vac withstand																																																																							
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	2200 Vac disconnection																																																																							
<p>V: High-energy varistor GSG: Specific gas tube Ft: Thermal fuse C: Remote signaling contact t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tbody> <tr> <td>Residual Current Leakage current to Ground</td> <td>Ipe</td> <td>None</td> </tr> <tr> <td>Follow current</td> <td>If</td> <td>None</td> </tr> <tr> <td>Nominal discharge current 15 x 8/20 μs impulses</td> <td>In</td> <td>15 kA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>I_{max}</td> <td>30 kA</td> </tr> <tr> <td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs</td> <td>Uoc</td> <td>6 kV</td> </tr> <tr> <td>Protection level @ In (8/20μs)</td> <td>Up</td> <td>4.0 kV</td> </tr> <tr> <td>Protection level @ In (8/20μs) and @ 6 kV (1.2/50 μs)</td> <td>Up</td> <td>5.0 kV</td> </tr> <tr> <td>Residual voltage at 5 kA @ 5 kA (8/20μs)</td> <td>Up-5kA</td> <td>3.2 kV</td> </tr> <tr> <td>Admissible short-circuit current</td> <td>Iscrc</td> <td>25 000 A</td> </tr> </tbody> </table>	Residual Current Leakage current to Ground	Ipe	None	Follow current	If	None	Nominal discharge current 15 x 8/20 μs impulses	In	15 kA	Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	30 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	6 kV	Protection level @ In (8/20μs)	Up	4.0 kV	Protection level @ In (8/20μs) and @ 6 kV (1.2/50 μs)	Up	5.0 kV	Residual voltage at 5 kA @ 5 kA (8/20μs)	Up-5kA	3.2 kV	Admissible short-circuit current	Iscrc	25 000 A																																													
Residual Current Leakage current to Ground	Ipe	None																																																																							
Follow current	If	None																																																																							
Nominal discharge current 15 x 8/20 μs impulses	In	15 kA																																																																							
Max. discharge current max. withstand @ 8/20 μs by pole	I _{max}	30 kA																																																																							
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50μs - 8/20μs	Uoc	6 kV																																																																							
Protection level @ In (8/20μs)	Up	4.0 kV																																																																							
Protection level @ In (8/20μs) and @ 6 kV (1.2/50 μs)	Up	5.0 kV																																																																							
Residual voltage at 5 kA @ 5 kA (8/20μs)	Up-5kA	3.2 kV																																																																							
Admissible short-circuit current	Iscrc	25 000 A																																																																							
	<table border="1"> <thead> <tr> <th colspan="3">Mechanical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Technology</td> <td></td> <td>VG Technology (MOV+GSG)</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>3-phase</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminals: 2.5-25mm² (35mm² rigid)</td> </tr> <tr> <td>Format</td> <td></td> <td>Monobloc modular box</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Disconnection from AC network</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>1 mechanical indicator - Red/Green</td> </tr> <tr> <td>Remote signaling of disconnection</td> <td></td> <td>Output on changeover contact</td> </tr> <tr> <td>Wiring for remote signaling</td> <td></td> <td>1.5 mm² max.</td> </tr> <tr> <td>Max. Voltage/Current for remote signaling</td> <td></td> <td>250 V / 0.5 A (AC) / 30 V / 3 A (DC)</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram - 6TE (EN43880)</td> </tr> <tr> <td>Weight</td> <td></td> <td>0.749 kg</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="3">Disconnectors</th> </tr> </thead> <tbody> <tr> <td>Thermal disconnecter</td> <td></td> <td>Internal</td> </tr> <tr> <td>Installation ground fault breaker</td> <td></td> <td>Type 'S' or delayed</td> </tr> <tr> <td>Back-up protection device</td> <td></td> <td>Fuses type gG - 50 A</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="3">Standards</th> </tr> </thead> <tbody> <tr> <td>Standards compliance</td> <td></td> <td>IEC 61643-11 / EN 61643-11 / UL1449 ed.5</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="3">Part number</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td>29423032</td> </tr> </tbody> </table>	Mechanical Characteristics			Technology		VG Technology (MOV+GSG)	SPD configuration		3-phase	Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)	Format		Monobloc modular box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection from AC network	Disconnection indicator		1 mechanical indicator - Red/Green	Remote signaling of disconnection		Output on changeover contact	Wiring for remote signaling		1.5 mm ² max.	Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)	Dimensions		See diagram - 6TE (EN43880)	Weight		0.749 kg	Disconnectors			Thermal disconnecter		Internal	Installation ground fault breaker		Type 'S' or delayed	Back-up protection device		Fuses type gG - 50 A	Standards			Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5	Part number					29423032
Mechanical Characteristics																																																																									
Technology		VG Technology (MOV+GSG)																																																																							
SPD configuration		3-phase																																																																							
Connection to Network		By screw terminals: 2.5-25mm ² (35mm ² rigid)																																																																							
Format		Monobloc modular box																																																																							
Mounting		Symmetrical rail 35 mm (EN 60715)																																																																							
Housing material		Thermoplastic UL94 V-0																																																																							
Operating temperature	Tu	-40/+85°C																																																																							
Protection rating		IP20																																																																							
Failsafe mode		Disconnection from AC network																																																																							
Disconnection indicator		1 mechanical indicator - Red/Green																																																																							
Remote signaling of disconnection		Output on changeover contact																																																																							
Wiring for remote signaling		1.5 mm ² max.																																																																							
Max. Voltage/Current for remote signaling		250 V / 0.5 A (AC) / 30 V / 3 A (DC)																																																																							
Dimensions		See diagram - 6TE (EN43880)																																																																							
Weight		0.749 kg																																																																							
Disconnectors																																																																									
Thermal disconnecter		Internal																																																																							
Installation ground fault breaker		Type 'S' or delayed																																																																							
Back-up protection device		Fuses type gG - 50 A																																																																							
Standards																																																																									
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																																							
Part number																																																																									
		29423032																																																																							

