



- ▶ POE++ Compatible (IEEE 802.3bt) -10Gb (5-100m) with Cat6A S/FTP cabling
- ▶ Shielded RJ45 connectors
- ▶ Outdoor applications, IP54 (NEMA 3)
- ▶ Plastic enclosure, UL94-V0
- ▶ Conforms to IEC/EN 61643-21
- ▶ SPD categories D1, C3, C2



	Electrical Characteristics																																																													
	<table border="1"> <tr> <td>Network</td> <td></td> <td>10Gb/s on Cat6A S/FTP cabling</td> </tr> <tr> <td>Protection modes (network)</td> <td></td> <td>CM (Common Mode)</td> </tr> <tr> <td>Protection modes (POE)</td> <td></td> <td>CM (Common Mode)</td> </tr> <tr> <td>Transmission standard</td> <td></td> <td>IEEE 802.3bt</td> </tr> <tr> <td>Lightning Protection Zones (LPZ)</td> <td></td> <td>0 - 2</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>8 Vdc</td> </tr> <tr> <td>Max. operating voltage (POE)</td> <td>Uc</td> <td>60 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>500 MHz</td> </tr> <tr> <td>Max. data rate</td> <td></td> <td>10 Gbps</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>2 A</td> </tr> <tr> <td>Max. POE power (4PPOE)</td> <td></td> <td>90 W</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs, X-C (Line/Earth)</td> <td>I_{max}</td> <td>2 kA</td> </tr> <tr> <td>Protection Level C3 category (10/1000μs), 300 applications@10 A, X-X (Line/Line)</td> <td>Up</td> <td>700 V</td> </tr> <tr> <td>Protection level C3 category (10/1000μs), 300 applications@10 A, X-C (Line/Earth)</td> <td>Up</td> <td>700 V</td> </tr> <tr> <td>Protection Level C3 Category (10/1000μs), 300 applications @ 10A, (Pair-Pair, POE)</td> <td>Up</td> <td>700 V</td> </tr> <tr> <td>Impulse current D1 category (10/350μs), 2 applications, X-C (Line/Earth)</td> <td>I_{imp}</td> <td>500 A</td> </tr> <tr> <td>Nominal Discharge Current C2 category (8/20μs), 10 applications, X-X (Line/Line)</td> <td>I_n</td> <td>4 kV / 2 kA</td> </tr> <tr> <td>Nominal discharge current C2 category (8/20μs), 10 applications X-C (Line/Earth)</td> <td>I_n</td> <td>4 kV / 2 kA</td> </tr> <tr> <td>Line resistance (± 10%)</td> <td></td> <td>0 Ohm</td> </tr> <tr> <td>Capacitance @1MHz, X-C (Line/Earth)</td> <td>C</td> <td>< 5 pF</td> </tr> </table>		Network		10Gb/s on Cat6A S/FTP cabling	Protection modes (network)		CM (Common Mode)	Protection modes (POE)		CM (Common Mode)	Transmission standard		IEEE 802.3bt	Lightning Protection Zones (LPZ)		0 - 2	Max. DC operating voltage	Uc	8 Vdc	Max. operating voltage (POE)	Uc	60 Vdc	Max. frequency	f max.	500 MHz	Max. data rate		10 Gbps	Max. load current @25°C	IL	2 A	Max. POE power (4PPOE)		90 W	Max. discharge current max. withstand @ 8/20 μs, X-C (Line/Earth)	I _{max}	2 kA	Protection Level C3 category (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up	700 V	Protection level C3 category (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up	700 V	Protection Level C3 Category (10/1000μs), 300 applications @ 10A, (Pair-Pair, POE)	Up	700 V	Impulse current D1 category (10/350μs), 2 applications, X-C (Line/Earth)	I _{imp}	500 A	Nominal Discharge Current C2 category (8/20μs), 10 applications, X-X (Line/Line)	I _n	4 kV / 2 kA	Nominal discharge current C2 category (8/20μs), 10 applications X-C (Line/Earth)	I _n	4 kV / 2 kA	Line resistance (± 10%)		0 Ohm	Capacitance @1MHz, X-C (Line/Earth)	C	< 5 pF
Network		10Gb/s on Cat6A S/FTP cabling																																																												
Protection modes (network)		CM (Common Mode)																																																												
Protection modes (POE)		CM (Common Mode)																																																												
Transmission standard		IEEE 802.3bt																																																												
Lightning Protection Zones (LPZ)		0 - 2																																																												
Max. DC operating voltage	Uc	8 Vdc																																																												
Max. operating voltage (POE)	Uc	60 Vdc																																																												
Max. frequency	f max.	500 MHz																																																												
Max. data rate		10 Gbps																																																												
Max. load current @25°C	IL	2 A																																																												
Max. POE power (4PPOE)		90 W																																																												
Max. discharge current max. withstand @ 8/20 μs, X-C (Line/Earth)	I _{max}	2 kA																																																												
Protection Level C3 category (10/1000μs), 300 applications@10 A, X-X (Line/Line)	Up	700 V																																																												
Protection level C3 category (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up	700 V																																																												
Protection Level C3 Category (10/1000μs), 300 applications @ 10A, (Pair-Pair, POE)	Up	700 V																																																												
Impulse current D1 category (10/350μs), 2 applications, X-C (Line/Earth)	I _{imp}	500 A																																																												
Nominal Discharge Current C2 category (8/20μs), 10 applications, X-X (Line/Line)	I _n	4 kV / 2 kA																																																												
Nominal discharge current C2 category (8/20μs), 10 applications X-C (Line/Earth)	I _n	4 kV / 2 kA																																																												
Line resistance (± 10%)		0 Ohm																																																												
Capacitance @1MHz, X-C (Line/Earth)	C	< 5 pF																																																												
Mechanical Characteristics																																																														
<table border="1"> <tr> <td>Technology</td> <td>Gas discharge tube</td> </tr> <tr> <td>SPD configuration</td> <td>8 wires+shielded</td> </tr> <tr> <td>Connection to Network</td> <td>RJ45 shielded connectors Female input/output</td> </tr> <tr> <td>Cable glands</td> <td>Rubber</td> </tr> <tr> <td>Format</td> <td>Plastic Box with connectors input/output</td> </tr> <tr> <td>Mounting</td> <td>Wall / Pole / Plate</td> </tr> <tr> <td>Housing material</td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu -40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td>IP54</td> </tr> <tr> <td>Failsafe mode</td> <td>Short-circuit - transmission cut-off - fault mode 2</td> </tr> <tr> <td>Pinout</td> <td>(1-2)(3-6)(4-5)(7-8)</td> </tr> <tr> <td>Dimensions</td> <td>See diagram</td> </tr> <tr> <td>Weight</td> <td>0.14 kg / 0.31 lbs</td> </tr> </table>	Technology	Gas discharge tube	SPD configuration	8 wires+shielded	Connection to Network	RJ45 shielded connectors Female input/output	Cable glands	Rubber	Format	Plastic Box with connectors input/output	Mounting	Wall / Pole / Plate	Housing material	Thermoplastic UL94 V-0	Operating temperature	Tu -40/+85°C	Protection rating	IP54	Failsafe mode	Short-circuit - transmission cut-off - fault mode 2	Pinout	(1-2)(3-6)(4-5)(7-8)	Dimensions	See diagram	Weight	0.14 kg / 0.31 lbs																																				
Technology	Gas discharge tube																																																													
SPD configuration	8 wires+shielded																																																													
Connection to Network	RJ45 shielded connectors Female input/output																																																													
Cable glands	Rubber																																																													
Format	Plastic Box with connectors input/output																																																													
Mounting	Wall / Pole / Plate																																																													
Housing material	Thermoplastic UL94 V-0																																																													
Operating temperature	Tu -40/+85°C																																																													
Protection rating	IP54																																																													
Failsafe mode	Short-circuit - transmission cut-off - fault mode 2																																																													
Pinout	(1-2)(3-6)(4-5)(7-8)																																																													
Dimensions	See diagram																																																													
Weight	0.14 kg / 0.31 lbs																																																													
Standards																																																														
Standards compliance	IEC 61643-21 / EN 61643-21 / UL497B / IEEE 802.3af/3at/3bt, ANSI/TIA-568-c.1																																																													
Part number																																																														
581549																																																														

