





NEW CITEL PV SPD

- Combined SPD type 1+2+3
- CTC-Technology
- Discharge capacity per pole: limp/total= 6.25/12.5 kA (10/350 µs); In/total= 15 /60 kA (8/20 µs)
- Safe disconnecting device
- Fault-resistant Y-circuit
- Remote signaling
- Complies with the IEC 61643-11, EN 61643-11, EN 50539-11 and UTE C 61-740-51 standards



V: High-energy varistor

Ft: Thermal fuse

C: Remote signal contact

t°: Thermal disconnection system

MI: Mechanical disconnection indicator

Electrical Characteristics

| | | |
|---|--------------------------|----------|
| SPD type | 1+2+3 | |
| Network | PV 1500 Vdc | |
| Nominal PV voltage | Uocstc | 1250 Vdc |
| Max. PV operating voltage | Ucpv | 1500 Vdc |
| Residual Current Leakage current to Ground | Ipe | < 0.1 mA |
| PV Permanent Operating current Current consumption at Ucpv | Icpv | < 0.1 mA |
| Follow current | If | None |
| Nominal discharge current 15 x 8/20 µs impulses | In | 20 kA |
| Max. discharge current max. withstand @ 8/20 µs by pole | Imax | 40 kA |
| Total Maximum discharge current max. total withstand @ 8/20 µs | Imax Total | 60 kA |
| Impulse current by pole max. withstand 10/350µs by pole | Iimp | 6.25 kA |
| Total lightning current max. total withstand @ 10/350µs | Itotal | 12.5 kA |
| Current withstand short circuit PV | Iscpv | 15 000 A |
| Connection mode(s) | +/-/PE | |
| Protection mode(s) | Common/Differential mode | |
| Protection level +/- @ In (8/20µs) | Up | 4.8 kV |
| Protection level +/PE (-/PE) @ In (8/20µs) | Up | 4.8 kV |

Mechanical Characteristics

| | | |
|---|--|-----------|
| Technology | MOV | |
| Connection to Network | By screw terminals: 2.5-25mm² (35mm²) / by bus | |
| Format | Compact monobloc box | |
| Mounting | Symmetrical rail 35 mm (EN 60715) | |
| Housing material | Thermoplastic UL94 V-0 | |
| Operating temperature | Tu | -40/+85°C |
| Protection rating | IP20 | |
| Failsafe mode | All pole disconnection from PV network | |
| Disconnection indicator | 1 mechanical indicator - Red/Green | |
| Remote signaling of disconnection | Output on changeover contact | |
| Max. Voltage/Current for remote signaling | 250 V / 0.5 A (AC) / 30 V / 3 A (DC) | |
| Dimensions | See diagram - 2.5TE (EN43880) | |
| Weight | 0.500 kg | |
| Disconnectors | | |
| Thermal disconnector | CTC Technology integrated | |
| Back-up protection device | Without | |
| Standards | | |
| Standards compliance | IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5 | |
| Part number | 65212103 | |

