



Type 1+2+3 PV surge protector - CTC Technology

CITEL



DPVN1-6CVGS-21Y-1500



NEW CITEL PV SPD



- Type 1+2+3 surge protector for Photovoltaic
- CTC Technology
- VG Technology
- Impulse currents Iimp/Itotal: 6.25/12.5 kA (10/350μs)
- Common/Differential mode protection
- Remote signaling
- IEC 61643-31, EN 61643-31, EN 50539-11, UL1449 ed.5 compliance



V: High-energy varistor
GSG: Specific gas tube
Ft: Thermal fuse
C: Remote signaling contact
t*: Thermal disconnection system
MI: Mechanical status indicator

Electrical Characteristics

SPD type	1+2+3	
Network	PV 1500 Vdc	
Nominal PV voltage	Uocstc	1250 Vdc
Max. PV operating voltage	Ucpv	1500 Vdc
Residual Current <i>Leakage current to Ground</i>	Ipe	None
PV Permanent Operating current <i>Current consumption at Ucpv</i>	Icpv	None
Follow current	If	None
Nominal discharge current <i>15 x 8/20 μs impulses</i>	In	20 kA
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	Imax	40 kA
Total Maximum discharge current <i>max. total withstand @ 8/20 μs</i>	Imax Total	60 kA
Impulse current by pole <i>max. withstand 10/350μs by pole</i>	Iimp	6.25 kA
Total lightning current <i>max. total withstand @ 10/350μs</i>	Itotal	12.5 kA
Withstand on Combination waveform IEC 61643-11 <i>Class III test: 1.2/50μs - 8/20μs</i>	Uoc	6 kV
Current withstand short circuit PV	Iscpv	15 000 A
Connection mode(s)	+/-/PE	
Protection mode(s)	Common/Differential mode	
Protection level +/- <i>@ In (8/20μs)</i>	Up	4.8 kV
Protection level +/PE (-/PE) <i>@ In (8/20μs)</i>	Up	4.8 kV

Mechanical Characteristics

Technology	VG Technology (MOV+GSG)	
Connection to Network	By screw terminals: 2.5-25mm ² (35mm ²) / by bus	
Format	Compact monobloc box	
Mounting	Symmetrical rail 35 mm (EN 60715)	
Housing material	Thermoplastic UL94 V-0	
Operating temperature	Tu	-40/+85°C
Protection rating	IP20	
Failsafe mode	All pole disconnection from PV network	
Disconnection indicator	1 mechanical indicator - Red/Green	
Remote signaling of disconnection	Output on changeover contact	
Max. Voltage/Current for remote signaling	250 V / 0.5 A (AC) / 30 V / 3 A (DC)	
Dimensions	See diagram - 2.5TE (EN43880)	
Weight	0.510 kg	
Disconnectors		
Thermal disconnector	CTC Technology integrated	
Back-up protection device	Without	
Standards		
Standards compliance	IEC 61643-31 / EN 61643-31 / EN 50539-11 / UL1449 ed.5	
Part number	65222103	

