



Electrical Characteristics		
SPD type		2+3
Network		PV network 1000 Vdc
Nominal DC voltage	Un-dc	1000 Vdc
Rated insulation voltage <i>U_i</i>	U _i	1000 Vdc
Rated current <i>I_{nA}</i>	I _{nA}	32 A
Rated string current <i>I_{nC}</i>	I _{nC}	16 A
Mechanical Characteristics		
Dimensions		See diagram
Weight		1.648 kg
Input / per MPPT		Spring clamp terminals / 4x16mm ²
Output / per MPPT		Spring terminals / 2x 6-16mm ²
Ground connection terminal		Screw terminal 6-35mm ²
Cable gland		14x M16 (Ø 4,5-10 mm)
Housing material		UV and ozone resistant, fiberglass reinforced polycarbonate with semi-transparent cover
Dimensions		WxHxD (mm): 254 x 180 x 111
Ambient temperatures		Indoor: -5°C to max. +40°C (+35°C 24h average) / Outdoor: -25°C to max. +40°C (+35°C 24h average)
Humidity		Indoor: max. 50% at +40°C, max. 90% at 20°C (non-condensing) / Outdoor: 95% for a short time at +25°C (non-condensing)
Protection rating		IP 65
Protection class		Class II
Impact resistance		IK 8
Pressure compensation element		Existing
Standards		
Standards compliance		DIN EN 50539-11 / DIN EN IEC 61439-2
Part number		
157206		

