



| Electrical Characteristics    |       |  |
|-------------------------------|-------|--|
| SPD type                      |       | 1+2+3  |
| Network                       |       | PV network 1000 Vdc  |
| Nominal DC voltage            | Un-dc | 1000 Vdc   |
| Rated insulation voltage      | Ui    | 1000 Vdc   |
| Rated current                 | InA   | 32 A   |
| Rated string current          | InC   | 16 A   |
| Mechanical Characteristics    |       |  |
| Dimensions                    |       | See diagram  |
| Weight                        |       | 1.648 kg   |
| Input / per MPPT              |       | Spring clamp terminals / 4x16mm <sup>2</sup>   |
| Output / per MPPT             |       | Spring terminals / 2x 6-16mm <sup>2</sup>  |
| Ground connection terminal    |       | Screw terminal 6-35mm <sup>2</sup>   |
| Cable gland                   |       | 14x M16 (Ø 4,5-10 mm)  |
| Housing material              |       | UV and ozone resistant, fiberglass reinforced polycarbonate with semi-transparent cover                                |
| Dimensions                    |       | WxHxD (mm): 254 x 180 x 111  |
| Ambient temperatures          |       | Indoor: -5°C to max. +40°C (+35°C 24h average) / Outdoor: -25°C to max. +40°C (+35°C 24h average)                      |
| Humidity                      |       | Indoor: max. 50% at +40°C, max. 90% at 20°C (non-condensing) / Outdoor: 95% for a short time at +25°C (non-condensing) |
| Protection rating             |       | IP 65  |
| Protection class              |       | Class II   |
| Impact resistance             |       | IK 8   |
| Pressure compensation element |       | Existing   |
| Standards                     |       |  |
| Standards compliance          |       | DIN EN 50539-11 / DIN EN IEC 61439-2   |
| Part number                   |       |  |
| 157208                        |       |  |

