



2-pair Data surge protector unit

CITEL

B280-48DBC



- 2-pair surge protection unit
- 48 V
- Removable protection circuit
- Wall mounting and screw connection
- UL497 A&B



	Electrical Characteristics																									
<p>Gb: 3-electrode gas tube R: Resistor DBC: 3-pole low capacitance diode</p>	Mechanical Characteristics																									
	<table border="1"> <tbody> <tr><td>Technology</td><td>GDT+Clamping diode</td></tr> <tr><td>SPD configuration</td><td>2 pairs</td></tr> <tr><td>Connection to Network</td><td>By screw terminal: cross section 0.4-1.5mm²</td></tr> <tr><td>Format</td><td>Wall mounting box</td></tr> <tr><td>Mounting</td><td>Wall mounting by screws (not supplied)</td></tr> <tr><td>Housing material</td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu -40/+85°C</td></tr> <tr><td>Protection rating</td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td>Short-circuit - transmission cut-off - fault mode 2</td></tr> <tr><td>Spare module(s)</td><td>S280-48DBC</td></tr> <tr><td>Dimensions</td><td>See diagram</td></tr> <tr><td>Weight</td><td>0.043 kg</td></tr> </tbody> </table>	Technology	GDT+Clamping diode	SPD configuration	2 pairs	Connection to Network	By screw terminal: cross section 0.4-1.5mm ²	Format	Wall mounting box	Mounting	Wall mounting by screws (not supplied)	Housing material	Thermoplastic UL94 V-0	Operating temperature	Tu -40/+85°C	Protection rating	IP20	Failsafe mode	Short-circuit - transmission cut-off - fault mode 2	Spare module(s)	S280-48DBC	Dimensions	See diagram	Weight	0.043 kg	
Technology	GDT+Clamping diode																									
SPD configuration	2 pairs																									
Connection to Network	By screw terminal: cross section 0.4-1.5mm ²																									
Format	Wall mounting box																									
Mounting	Wall mounting by screws (not supplied)																									
Housing material	Thermoplastic UL94 V-0																									
Operating temperature	Tu -40/+85°C																									
Protection rating	IP20																									
Failsafe mode	Short-circuit - transmission cut-off - fault mode 2																									
Spare module(s)	S280-48DBC																									
Dimensions	See diagram																									
Weight	0.043 kg																									
	Standards																									
	<table border="1"> <tbody> <tr><td>Standards compliance</td><td>IEC 61643-21 / EN 61643-21 / UL497A</td></tr> <tr><td>Certification</td><td>UL 497B</td></tr> </tbody> </table>	Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A	Certification	UL 497B																					
Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A																									
Certification	UL 497B																									
	Part number																									
	72754																									

