



2-pair monobloc Data surge protector

CITEL

DLU2-24DBC



- For DIN rail mounting
- Monobloc housing
- 2-pair
- Un: 24 V
- IEC 61643-21 compliance
- UL497A



	Electrical Characteristics																																											
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr><td>Network</td><td></td><td>24 V line, High bitrate</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>24 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>28 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 20 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>300 mA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax</td><td>20 kA</td></tr> <tr><td>Line inductance</td><td></td><td>No</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common/Differential mode</td></tr> <tr><td>Protection level Following the test category C3 (IEC61643-21) - Line/Line</td><td>Up</td><td>50 V</td></tr> <tr><td>Max. capacitance</td><td>C</td><td>< 50 pF</td></tr> <tr><td>Impulse current 2 x 10/350 μs Test - D1 Category</td><td>Iimp</td><td>5 kA</td></tr> <tr><td>Nominal discharge current C2 Category</td><td>In</td><td>5 kA</td></tr> <tr><td>Line resistance</td><td></td><td>< 4.7 Ohm</td></tr> </table>		Network		24 V line, High bitrate	Nominal line voltage	Un	24 V	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 20 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance		No	Protection mode(s)		Common/Differential mode	Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	50 V	Max. capacitance	C	< 50 pF	Impulse current 2 x 10/350 μs Test - D1 Category	Iimp	5 kA	Nominal discharge current C2 Category	In	5 kA	Line resistance		< 4.7 Ohm
Network		24 V line, High bitrate																																										
Nominal line voltage	Un	24 V																																										
Max. DC operating voltage	Uc	28 Vdc																																										
Max. frequency	f max.	> 20 MHz																																										
Insertion loss		< 1 dB																																										
Max. load current @25°C	IL	300 mA																																										
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																										
Line inductance		No																																										
Protection mode(s)		Common/Differential mode																																										
Protection level Following the test category C3 (IEC61643-21) - Line/Line	Up	50 V																																										
Max. capacitance	C	< 50 pF																																										
Impulse current 2 x 10/350 μs Test - D1 Category	Iimp	5 kA																																										
Nominal discharge current C2 Category	In	5 kA																																										
Line resistance		< 4.7 Ohm																																										
Mechanical Characteristics																																												
<table border="1"> <tr><td>Technology</td><td>GDT+Clamping diode</td></tr> <tr><td>SPD configuration</td><td>2 pairs</td></tr> <tr><td>Connection to Network</td><td>By screw terminal - cross section 1.5-2.5mm²</td></tr> <tr><td>Format</td><td>DIN box</td></tr> <tr><td>Mounting</td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu -40/+85°C</td></tr> <tr><td>Protection rating</td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td>Short-circuit</td></tr> <tr><td>Disconnection indicator</td><td>Transmission interrupt - default mode 2</td></tr> <tr><td>Remote signaling of disconnection</td><td>No</td></tr> <tr><td>Dimensions</td><td>See diagram</td></tr> <tr><td>Weight</td><td>0.063 kg</td></tr> </table>		Technology	GDT+Clamping diode	SPD configuration	2 pairs	Connection to Network	By screw terminal - cross section 1.5-2.5mm ²	Format	DIN box	Mounting	Symmetrical rail 35 mm (EN 60715)	Housing material	Thermoplastic UL94 V-0	Operating temperature	Tu -40/+85°C	Protection rating	IP20	Failsafe mode	Short-circuit	Disconnection indicator	Transmission interrupt - default mode 2	Remote signaling of disconnection	No	Dimensions	See diagram	Weight	0.063 kg																	
Technology	GDT+Clamping diode																																											
SPD configuration	2 pairs																																											
Connection to Network	By screw terminal - cross section 1.5-2.5mm ²																																											
Format	DIN box																																											
Mounting	Symmetrical rail 35 mm (EN 60715)																																											
Housing material	Thermoplastic UL94 V-0																																											
Operating temperature	Tu -40/+85°C																																											
Protection rating	IP20																																											
Failsafe mode	Short-circuit																																											
Disconnection indicator	Transmission interrupt - default mode 2																																											
Remote signaling of disconnection	No																																											
Dimensions	See diagram																																											
Weight	0.063 kg																																											
Standards																																												
<table border="1"> <tr><td>Standards compliance</td><td>IEC 61643-21 / EN 61643-21 / UL497A</td></tr> <tr><td>Certification</td><td>UL 497B</td></tr> </table>		Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A	Certification	UL 497B																																							
Standards compliance	IEC 61643-21 / EN 61643-21 / UL497A																																											
Certification	UL 497B																																											
Part number																																												
640433																																												

