





## Type 1+2 AC surge protector - 3-phase

# CITEL

### DUT250VG-300/TNC



- ↳ Type 1+2+3, 3-phase surge protector
- ↳ Common and differential mode
- ↳ Very compact monobloc enclosure
- ↳ Iimp by pole/total : 25kA
- ↳ Internal disconnection, status indicator
- ↳ Optimized to TOV
- ↳ EN 61643-11, IEC 61643-11 and UL1449 ed.5 compliance



V: High-energy varistor  
 GSG: Specific Gas Tube  
 Ft: Thermal fuse  
 t\*: Thermal disconnection system  
 MI: Disconnection indicator

#### Electrical Characteristics

SPD type	1+2+3
Network	230/400 V 3-phase
AC system	TNC
Nominal line voltage	Un 230/400 Vac
Max. AC operating voltage	Uc 255 Vac
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT 335 Vac withstand
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT 440 Vac withstand
Residual Current Leakage current to Ground	Ipe None
Follow current	If None
Nominal discharge current 15 x 8/20 μs impulses	In 40 kA
Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub> 100 kA
Impulse current by pole max. withstand 10/350 μs by pole	I <sub>imp</sub> 25 kA
Total lightning current max. total withstand @ 10/350 μs	I <sub>total</sub> 75 kA
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50 μs - 8/20 μs	Uoc 6 kV
Withstand on overvoltages IEEE C62.41.1	20 kV
Specific energy by pole max. withstand 10/350 μs	W/R 156 kJ/ohm
Connection mode(s)	L/PEN
Protection mode(s)	Common mode
Protection level L/PE @ In (8/20 μs)	Up L/PE 1.5 kV
Admissible short-circuit current	I <sub>sc</sub> 50 000 A

#### Mechanical Characteristics

Technology	VG Technology (MOV+GSG)
SPD configuration	3-phase
Connection to Network	By screw terminals: 6-35mm <sup>2</sup> / by bus
Format	Multipolar modular box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	T <sub>u</sub> -40/+85°C
Protection rating	IP20
Disconnection indicator	3 mechanical indicators by pole
Remote signaling of disconnection	none
Dimensions	See diagram
Weight	0.61 kg

#### Disconnectors

Thermal disconnector	Internal
Installation ground fault breaker	Type 'S' or delayed
Back-up protection device	Fuse assembly: SFD1-25-30S / or Fuses Type gG 315 A

#### Standards

Standards compliance	IEC 61643-11 / EN 61643-11 / UL1449 ed.5
Certification	

#### Part number

3588

