





- Din rail plug-in surge protector
- 2-pair
- Un: 48 V
- Shield wire protection
- Without line cut-off
- IEC 61643-21 compliance
- UL497B



	<b>Electrical Characteristics</b>																																								
 <p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RNIS-T0, 48 V line</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>48 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>53 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>&gt; 3 MHz</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>Imax</td> <td>20 kA</td> </tr> <tr> <td>Line inductance</td> <td></td> <td>No</td> </tr> <tr> <td>Protection level @ In (8/20 μs)</td> <td>Up L/L</td> <td>70 V</td> </tr> <tr> <td>Impulse current 2 x 10/350μs Test - D1 Category</td> <td>limp</td> <td>5 kA</td> </tr> <tr> <td>Nominal discharge current C2 Category</td> <td>In</td> <td>5 kA</td> </tr> </table>		Network		RNIS-T0, 48 V line	Nominal line voltage	Un	48 V	Max. DC operating voltage	Uc	53 Vdc	Max. frequency	f max.	> 3 MHz	Max. load current @25°C	IL	300 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA	Line inductance		No	Protection level @ In (8/20 μs)	Up L/L	70 V	Impulse current 2 x 10/350μs Test - D1 Category	limp	5 kA	Nominal discharge current C2 Category	In	5 kA									
Network		RNIS-T0, 48 V line																																							
Nominal line voltage	Un	48 V																																							
Max. DC operating voltage	Uc	53 Vdc																																							
Max. frequency	f max.	> 3 MHz																																							
Max. load current @25°C	IL	300 mA																																							
Max. discharge current max. withstand @ 8/20 μs by pole	Imax	20 kA																																							
Line inductance		No																																							
Protection level @ In (8/20 μs)	Up L/L	70 V																																							
Impulse current 2 x 10/350μs Test - D1 Category	limp	5 kA																																							
Nominal discharge current C2 Category	In	5 kA																																							
	<b>Mechanical Characteristics</b>																																								
	<table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>2-pairs+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminal: cross section 0.5-2.5mm<sup>2</sup></td> </tr> <tr> <td>Format</td> <td></td> <td>Plug-in DIN box</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Symmetrical rail 35 mm (EN 60715)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating and storage temperature</td> <td></td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit</td> </tr> <tr> <td>Disconnection indicator</td> <td></td> <td>Transmission interrupt - default mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td>DLA2M-48D3</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> <tr> <td>Weight</td> <td></td> <td>0.089 kg</td> </tr> </table>		Technology		GDT+Clamping diode	SPD configuration		2-pairs+shielded	Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>	Format		Plug-in DIN box	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating and storage temperature		-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit	Disconnection indicator		Transmission interrupt - default mode 2	Spare module(s)		DLA2M-48D3	Dimensions		See diagram	Weight		0.089 kg
Technology		GDT+Clamping diode																																							
SPD configuration		2-pairs+shielded																																							
Connection to Network		By screw terminal: cross section 0.5-2.5mm <sup>2</sup>																																							
Format		Plug-in DIN box																																							
Mounting		Symmetrical rail 35 mm (EN 60715)																																							
Housing material		Thermoplastic UL94 V-0																																							
Operating and storage temperature		-40/+85°C																																							
Protection rating		IP20																																							
Failsafe mode		Short-circuit																																							
Disconnection indicator		Transmission interrupt - default mode 2																																							
Spare module(s)		DLA2M-48D3																																							
Dimensions		See diagram																																							
Weight		0.089 kg																																							
	<b>Standards</b>																																								
	<table border="1"> <tr> <td>Standards compliance</td> <td></td> <td>IEC 61643-21 / EN 61643-21 / UL497B</td> </tr> <tr> <td>Certification</td> <td></td> <td>UL Listed</td> </tr> </table>		Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B	Certification		UL Listed																																	
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497B																																							
Certification		UL Listed																																							
	<b>Part number</b>																																								
	<table border="1"> <tr> <td>640312</td> </tr> </table>		640312																																						
640312																																									