



CITEL

Outdoor gigabit POE-A surge protector

CMJ8-POE-A-C5E



- Discover our latest innovation : the [CWMJ8-POE-C6A](#)
- POE ++ compatible surge protector
- Category 5E compatible
- Shielded RJ45 connectors
- Outdoor application: IP65
- Metal enclosure
- Compliant with IEC 61643-21, NF EN 61643-21
- UL497B certified



	Electrical Characteristics																																								
<p>P: 3-electrode GDT DBC: Low capacitance diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>Gigabit Ethernet (Cat.5E)</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>48 Vdc</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>60 Vdc - 650 mA</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>250 MHz</td> </tr> <tr> <td>Max. data rate</td> <td></td> <td>10/100/1000 Mbps</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>1200 mA</td> </tr> <tr> <td>Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i></td> <td>Up</td> <td>70 V</td> </tr> <tr> <td>Impulse current <i>2 x 10/350µs Test - D1 Category</i></td> <td>Iimp</td> <td>500 A</td> </tr> <tr> <td>Line/Line Nominal discharge current <i>C2 Category</i></td> <td>In L/L</td> <td>500 A</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) <i>8/20µs Test x 10 - C2 Category</i></td> <td>In L/PE</td> <td>2000 A</td> </tr> </table>		Network		Gigabit Ethernet (Cat.5E)	Nominal line voltage	Un	48 Vdc	Max. DC operating voltage	Uc	60 Vdc - 650 mA	Max. frequency	f max.	250 MHz	Max. data rate		10/100/1000 Mbps	Insertion loss		< 1 dB	Max. load current @25°C	IL	1200 mA	Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i>	Up	70 V	Impulse current <i>2 x 10/350µs Test - D1 Category</i>	Iimp	500 A	Line/Line Nominal discharge current <i>C2 Category</i>	In L/L	500 A	Nominal Discharge Current, X-C (Line/Earth) <i>8/20µs Test x 10 - C2 Category</i>	In L/PE	2000 A						
Network		Gigabit Ethernet (Cat.5E)																																							
Nominal line voltage	Un	48 Vdc																																							
Max. DC operating voltage	Uc	60 Vdc - 650 mA																																							
Max. frequency	f max.	250 MHz																																							
Max. data rate		10/100/1000 Mbps																																							
Insertion loss		< 1 dB																																							
Max. load current @25°C	IL	1200 mA																																							
Protection level <i>Following the test category C3 (IEC61643-21) - Line/Line</i>	Up	70 V																																							
Impulse current <i>2 x 10/350µs Test - D1 Category</i>	Iimp	500 A																																							
Line/Line Nominal discharge current <i>C2 Category</i>	In L/L	500 A																																							
Nominal Discharge Current, X-C (Line/Earth) <i>8/20µs Test x 10 - C2 Category</i>	In L/PE	2000 A																																							
	Mechanical Characteristics																																								
	<table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>8 wires+shielded</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>RJ45 shielded connectors Female input/output</td> </tr> <tr> <td>Format</td> <td></td> <td>Plastic Box with connectors input/output</td> </tr> <tr> <td>Mounting</td> <td></td> <td>On plate or pole</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP65</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit - transmission cut-off - fault mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td>CMJ8-POE-A-C5E/PCB</td> </tr> <tr> <td>Pinout</td> <td></td> <td>(1-2)(3-6)(4-5)(7-8)</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> <tr> <td>Weight</td> <td></td> <td>0.18 kg</td> </tr> </table>		Technology		GDT+Clamping diode	SPD configuration		8 wires+shielded	Connection to Network		RJ45 shielded connectors Female input/output	Format		Plastic Box with connectors input/output	Mounting		On plate or pole	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP65	Failsafe mode		Short-circuit - transmission cut-off - fault mode 2	Spare module(s)		CMJ8-POE-A-C5E/PCB	Pinout		(1-2)(3-6)(4-5)(7-8)	Dimensions		See diagram	Weight		0.18 kg
Technology		GDT+Clamping diode																																							
SPD configuration		8 wires+shielded																																							
Connection to Network		RJ45 shielded connectors Female input/output																																							
Format		Plastic Box with connectors input/output																																							
Mounting		On plate or pole																																							
Housing material		Thermoplastic UL94 V-0																																							
Operating temperature	Tu	-40/+85°C																																							
Protection rating		IP65																																							
Failsafe mode		Short-circuit - transmission cut-off - fault mode 2																																							
Spare module(s)		CMJ8-POE-A-C5E/PCB																																							
Pinout		(1-2)(3-6)(4-5)(7-8)																																							
Dimensions		See diagram																																							
Weight		0.18 kg																																							
	Standards																																								
	Standards compliance IEC 61643-21 / EN 61643-21 / IEEE 802-3an																																								
	Certification UL 497B																																								
	Part number																																								
	892002																																								

